

# 2" Artima/2

## Track Mounted LED Wallwasher

A2-W



W

### Applications

Artima/2 is a petite and powerful track-mounted luminaire, blending beauty and durability. The modern & lasting design of Artima is desired by contemporary, world-renowned museums.

### Features

- Lockable Aiming: Achieve 385° rotation, 0-90° tilt, and fully lock adjustment using hex keys
- A hammertone aluminum reflector and a 40° x 70° spread lens deliver an even floor-to-ceiling, side-to-side wash of light

### Wallwash (W)

- The internal reflector kicks light vertically up to the ceiling line and down to the floor, while the 40° x 70° spread lens extends the beam in two directions
- A uniquely designed lens and precisely spun reflector enables a 1:1 spacing ratio for unparallelled uniformity

**Complete Family** | Narrow Spot (A2-NSP), Wallwash (A2-W)

**Lumens** | 900, 1200, 1500, 2000

**CCT** | 27K, 30K, 35K, 40K, 50K

**CRI** | 90+ Standard, XIA-95+

**SDCM** | 2-Step MacAdam Ellipse

**Finish** | White, Black, Silver

**Dimming** | DIMTR, BLE

**Voltage** | 120V, 277V (Non-Dimmable)

**Control Capabilities** | Bluetooth

**Lifetime** | L70 at 50000 Hours

**Weight (lbs)** | 2

**Listing** | cSAus, c-UL-us



# 2" Artima/2

A2-W

## Track Mounted LED Wallwasher

EXAMPLE: **A2-W-900L-27K-90-DIMTR-120V-WH**

Series	Lumens	CCT	CRI	Driver	Voltage	Finish	Options	Optical Accessories
<b>A2-W</b>	<b>900L</b>	<b>27K</b>	<b>90+</b>	<b>DIMTR</b>	<b>120V</b>	<b>WH</b>	-	-
	<b>1200L</b>	<b>30K</b>	<b>XIA-95+</b>	<b>NON-DIM</b>	<b>277V</b>	<b>BK</b>	<b>SW</b>	<b>OA-A2-W-SL40X70</b>
	<b>1500L</b>	<b>35K</b>		<b>BLE</b>	<b>(Non-Dim Only)</b>	<b>SI</b>	<b>SB</b>	<b>OA-A2-W-LRS67</b>
	<b>2000L</b>	<b>40K</b>						<b>OA-A2-W-LRS50</b>
		<b>50K</b>						

**(50K Is Not Compatible with XIA-95+)**

**Note:** All extra optical accessories, aperture assemblies, and optics can be ordered separately. Check [EPL Website](#) for ordering nomenclature.

### Track Adaptor – Fully Concealed, Durable Locking

- Stainless steel clips lock fixture into our specially designed track systems. Two ‘click’ sounds indicate the fixture is secured into the track system
- Clips bite into aluminum, giving extremely durable ground connection
- Edison Price Lighting track systems are designed to completely conceal the adaptor for a clean profile
- Adaptors are shipped standard with all track fixtures. A Eutrac track adaptor can be used for mounting to Eutrac; 0-10V and DALI compatibility available. Contact factory for details

### Seamless Installation

Fixtures may be configured to mount to any Edison Price Lighting recessed, suspended, surface-mounted track systems.

### Anodized Construction

Heatsink is fabricated from extruded aluminum then undergoes a meticulous anodization process for a permanent and beautiful finish – increasing corrosion and heat resistance for long-lasting durability.

### Carefully Applied, Low-VOC Finish

All Edison Price Lighting track fixtures are painted standard with low-VOC water-based paint – diminishing the release of toxic fumes – enhancing air quality and occupant health (unlike solvent-based paint).

### Optical Accessories

- OA-A2-W-SL40X70** (40° x 70° Spread Lens) - Delivers a rectangular beam recommended for illuminating wider artwork
- OA-A2-W-LRS67** (67% Light Reduction Screen) - Reduces light by 67%, emitting 33% of total light; alternative to dimming
- OA-A2-W-LRS50** (50% Light Reduction Screen) - Reduces light by 50%, emitting 50% of total light; alternative to dimming
- OA-A2-W-DBL** (Daylight Blue) - Simulates daylight; ideal for museums, residential, & commercial
- OA-A2-W-PK** (Surprise Pink) - Complements skin tones; perfect for hospitality applications
- OA-A2-W-AMB** - Amber Color Filter
- OA-A2-W-BL** - Blue Color Filter
- OA-A2-W-GR** - Green Color Filter
- OA-A2-W-RD** - Red Color Filter
- OA-A2-W-RAL** (Rosco Custom Color) - Consult factory for a brilliant Rosco filter in any color. Click [here](#) to see more information on color filters selection

### XIA-95+ (Xicato)

- XTM Artist Series, XIM Integral Bluetooth Module (BLE + LED), or XOB (COB array light source in as small as 4.5mm form and up to 8300 lumens)
  - Best color-matching: within 1 x 2 MacAdam Ellipse
  - Up to 95+ CIE CRI
- Module varies by product family and fixture function.

### BLE Xicato XID Intelligent Drivers

Powered by Xicato XID (Intelligent Drivers), constant-current drivers that enable Bluetooth controls.

- Dimmable down to 0.1%
- Meets IEEE 1789 recommendations for flicker
- Group or individual remote control via a slide switch
- Bluetooth and IDM can be specified in the same fixture, to allow switching between the two options

### Driver

120/277V 50/60Hz; Flicker-free 1% dimming standard; THD < 20%; power factor >.09. Thermally protected. On/off rocker switch is mounted on the exterior of the driver box; included standard for 120V

### Dimming & Driver Information

**DIMTR** - Triac, incandescent, and electronic low voltage (ELV) dimming down to 5% in 120V only

**NON-DIM** - 120 or 277V Non-Dimming Control

**BLE** - Xicato XIM Bluetooth Integral Module/Xicato XID Intelligent Driver (Consult Factory For Info)

### Warranty

Five-year warranty not including providing extraordinary means of access, such as scaffolding or lifts, to service our products.

### Listings

- cSAus
- c-UL-us



# 2" Artima/2

Track Mounted LED Wallwasher

A2-W

