

3" Artima/3

Track Mounted LED Wallwasher

A3-W



W

Applications

Artima/3 is the most popular choice from our track selection, blending minimalism and functionality. The modern & lasting design of Artima is desired by contemporary, world-renowned museums.

Features

- Lockable Aiming: Achieve 385° rotation, 0-90° tilt, and fully lock adjustment using a hex key
- The optical assembly includes an aluminum reflector and a 40° x 70° spread lens that provides a scallop-free uniform floor-to-ceiling, side-to-side wash of light
- Assembly is keyed relative to luminaire housing to retain critical lens orientation
- On-off rocker switch located on the driver box comes standard

Wallwash (W)

- The internal reflector kicks light vertically up to the ceiling line and down to the floor, while the 40° x 70° spread lens extends the beam in two directions
- A uniquely designed lens and precisely spun reflector enables a 1:1 spacing ratio for unparalleled uniformity

Notable Projects

Mingei International Museum

Complete Family	Standard (A3), Narrow Spot (A3-NSP), Very Narrow Spot (A3-VNSP), Wallwash (A3-W)
Lumens	1200, 1500, 2000, 2500, 3000, 3500, 4000
CCT	27K, 30K, 35K, 40K, 50K
CRI	90+ Standard, XIA-95+
SDCM	2-Step MacAdam Ellipse
Finish	White, Black, Silver
Dimming	DIMTR, LTEA2W, BLE, DIMTR-IDM
Voltage	120V, 277V (Non-Dimmable)
Control Capabilities	IDM, Bluetooth
Lifetime	L70 at 50000 Hours
Weight (lbs)	3
Listing	cSAus, c-UL-us



3" Artima/3

A3-W

Track Mounted LED Wallwasher

EXAMPLE: **A3-W-1200L-27K-90-DIMTR-120V-WH**

Series	Lumens	CCT	CRI	Driver	Voltage	Finish	Optical Accessories
A3-W 1200L	27K	90+	DIMTR	120V	WH	-	
1500L	30K	XIA-95+	LTEA2W	277V	BK	OA-A3-W-SL40X70	
2000L	35K		NON-DIM	(Non-Dim Only)	SI	OA-A3-W-LRS67	
2500L	40K		BLE			OA-A3-W-LRS50	
3000L	50K		DIMTR-IDM				
3500L	(50K Is Not Compatible with XIA-95+)		(Integral Rotary Dimming Module)				
4000L							

Note: All extra optical accessories, aperture assemblies, and optics can be ordered separately. Check [EPL Website](#) for ordering nomenclature.

Interchangeable Optical Accessories

Assembly accepts up to 1 optical accessory to effortlessly alter the visual effect in the field.

Track Adaptor – Fully Concealed, Durable Locking

- Stainless steel clips lock fixture into our specially designed track systems. Two ‘click’ sounds indicate the fixture is secured into the track system
- Clips bite into aluminum, giving extremely durable ground connection
- Edison Price Lighting track systems are designed to completely conceal the adaptor for a clean profile
- Adaptors are shipped standard with all track fixtures. A Eutrac track adaptor can be used for mounting to Eutrac; 0-10V and DALI compatibility available. Contact factory for details

Seamless Installation

Fixtures may be configured to mount to any Edison Price Lighting recessed, suspended, surface-mounted track systems: [Sightline](#), [Highline](#), [Upline](#), [Autobus](#), [Eutrac](#), and [Unicep](#).

Anodized Construction

Heatsink is fabricated from extruded aluminum then undergoes a meticulous anodization process for a permanent and beautiful finish – increasing corrosion and heat resistance for long-lasting durability.

Carefully Applied, Low-VOC Finish

All Edison Price Lighting track fixtures are painted standard with low-VOC water-based paint – diminishing the release of toxic fumes – enhancing air quality and occupant health (unlike solvent-based paint).

Optical Accessories

- OA-A3-W-SL40X70** (40° x 70° Spread Lens) - Delivers a rectangular beam recommended for illuminating wider artwork
- OA-A3-W-LRS67** (67% Light Reduction Screen) - Reduces light by 67%, emitting 33% of total light; alternative to dimming
- OA-A3-W-LRS50** (50% Light Reduction Screen) - Reduces light by 50%, emitting 50% of total light; alternative to dimming
- OA-A3-W-DBL** (Daylight Blue) - Simulates daylight; ideal for museums, residential, & commercial
- OA-A3-W-PK** (Surprise Pink) - Complements skin tones; perfect for hospitality applications
- OA-A3-W-AMB** - Amber Color Filter
- OA-A3-W-BL** - Blue Color Filter
- OA-A3-W-GR** - Green Color Filter
- OA-A3-W-RD** - Red Color Filter
- OA-A3-W-RAL** (Rosco Custom Color) - Consult factory for a brilliant Rosco filter in any color. Click [here](#) to see more information on color filters selection

XIA-95+ (Xicato)

- XTM Artist Series, XIM Integral Bluetooth Module (BLE + LED), or XOB (COB array light source in as small as 4.5mm form and up to 8300 lumens)
 - Best color-matching: within 1 x 2 MacAdam Ellipse
 - Up to 95+ CIE CRI
- Module varies by product family and fixture function.

BLE Xicato Bluetooth Integral Module

Powered by Xicato XIM, the intelligent LED module controllable via a smart device with iOS- or Android-based apps.

- Dimmable down to 0.1%
- Meets IEEE 1789 recommendations for flicker
- Group or individual remote control via a slide switch
- Bluetooth and IDM can be specified in the same fixture, to allow switching between the two options

IDM (Integral Dimming Module) Option

- 120V track only; dim down to 10% using an integral rotary dimmer on the driver case
- Spring-loaded dimmer control shaft can be depressed flush with the driver case to enforce dimmer setting. ‘Clock face’ markings register dimmer setting

Driver

120/277V 50/60Hz; Flicker-free 1% dimming standard; THD < 20%; power factor >.09. Thermally protected. On/off rocker switch is mounted on the exterior of the driver box; included standard for 120V

Dimming & Driver Information

DIMTR - Triac, incandescent, and electronic low voltage (ELV) dimming down to 5% in 120V only

LTEA2W - Hi-lume 1% 2-Wire 120V Forward-Phase Control

NON-DIM - 120 or 277V Non-Dimming Control

BLE - Xicato XIM Bluetooth Integral Module/Xicato XID

Intelligent Driver (Consult Factory For Info)

DIMTR-IDM - Integral Rotary Dimming Module

Warranty

Five-year warranty not including providing extraordinary means of access, such as scaffolding or lifts, to service our products.

Listings

- cSAus
- c-UL-us



3" Artima/3

Track Mounted LED Wallwasher

A3-W

