



W

### Applications

Artima MRE W is a wallwasher designed for use with MR 16 retrofit LED lamps. The modern & lasting design of Artima is desired by contemporary, world-renowned museums.

### Features

- Lockable Aiming: Achieve 385° rotation, 0-90° tilt, and fully lock adjustment using hex keys
- The optical assembly consists of an internal specular reflector and a 40° x 70° spread lens. The assembly remains entirely undisturbed by relamping
- A socket cap prevents any backsplash of light onto the ceiling

### Wallwash (W)

- The internal reflector kicks light vertically up to the ceiling line and down to the floor, while the 40° x 70° spread lens extends the beam in two directions
- A uniquely designed lens and precisely spun reflector enables a 1:1 spacing ratio for unparallelled uniformity

### Notable Projects

Clark Art Institute

**Complete Family** | Wallwash (ART-MRE-W)

**SDCM** | 2-Step MacAdam Ellipse

**Finish** | White, Black, Silver, RAL

**Voltage** | 120V

**Lifetime** | L70 at 50000 Hours

**Listing** | cSAus, c-UL-us



## Track Mounted MR16 LED Wallwasher

EXAMPLE: **ART-MRE-W-120V-WH**

Series	Voltage	Finish	Sleeves	Options	Optical Accessories
<b>ART-MRE-W</b>	<b>120V</b>	<b>WH</b>	-	-	-
		<b>BK</b>	<b>WSLV</b>	<b>SW</b>	<b>OA-ART-MRE-W-SL40X70</b>
		<b>SI</b>	<b>BSLV</b>	<b>SB</b>	<b>OA-ART-MRE-W-LRS67</b>
		<b>RAL</b>			<b>OA-ART-MRE-W-LRS50</b>

**Note:** All extra optical accessories, aperture assemblies, and optics can be ordered separately. Check [EPL Website](#) for ordering nomenclature.

### Track Adaptor – Fully Concealed, Durable Locking

- Stainless steel clips lock fixture into our specially designed track systems. Two 'click' sounds indicate the fixture is secured into the track system
- Clips bite into aluminum, giving extremely durable ground connection
- Edison Price Lighting track systems are designed to completely conceal the adaptor for a clean profile
- Adaptors are shipped standard with all track fixtures. A Eutrac track adaptor can be used for mounting to Eutrac; 0-10V and DALI compatibility available. Contact factory for details

### Seamless Installation

Fixtures may be configured to mount to any Edison Price Lighting recessed, suspended, surface-mounted track systems: [Sightline](#), [Highline](#), [Upline](#), [Autobus](#), [Eutrac](#), and [Unicep](#).

### Anodized Construction

Heatsink is fabricated from extruded aluminum then undergoes a meticulous anodization process for a permanent and beautiful finish – increasing corrosion and heat resistance for long-lasting durability.

### Carefully Applied, Low-VOC Finish

All Edison Price Lighting track fixtures are painted standard with low-VOC water-based paint – diminishing the release of toxic fumes – enhancing air quality and occupant health (unlike solvent-based paint).

### Optical Accessories

- OA-ART-MRE-W-SL40X70** (40° x 70° Spread Lens) - Delivers a rectangular beam recommended for illuminating wider artwork
- OA-ART-MRE-W-LRS67** (67% Light Reduction Screen) - Reduces light by 67%, emitting 33% of total light; alternative to dimming
- OA-ART-MRE-W-LRS50** (50% Light Reduction Screen) - Reduces light by 50%, emitting 50% of total light; alternative to dimming
- OA-ART-MRE-W-DBL** (Daylight Blue) - Simulates daylight; ideal for museums, residential, & commercial
- OA-ART-MRE-W-PK** (Surprise Pink) - Complements skin tones; perfect for hospitality applications
- OA-ART-MRE-W-AMB** - Amber Color Filter
- OA-ART-MRE-W-BL** - Blue Color Filter
- OA-ART-MRE-W-GR** - Green Color Filter
- OA-ART-MRE-W-RD** - Red Color Filter
- OA-ART-MRE-W-RAL** (Rosco Custom Color) - Consult factory for a brilliant Rosco filter in any color. Click [here](#) to see more information on color filters selection

### Options

- Option for on/off rocker switch on the side of the transformer case

### Driver

Fixture is cULus-listed for mounting on Edison Price Lighting 120V track only.

### Warranty

Five-year warranty not including providing extraordinary means of access, such as scaffolding or lifts, to service our products.

### Listings

- cSAus
- c-UL-us

