

3"

BOLD-3-CYL-UWM

3" Up Down Wall Mount Architectural Cylinders

Bold Cylinders Series



#### APPLICATION & FEATURES

BOLD-3-CYL-UWM A small-profile architectural LED cylinder pendant luminaire featuring a modern die-cast design with a 3" round or square aperture. Offered in open, lensed downlight, and wallwash trim options, it delivers glare-free, high-quality illumination for general lighting needs. With a broad range of color temperatures supporting cool to warm tones, it integrates into any design and is well suited for commercial, retail, hospitality, and high-end residential applications.

This cylinder provides exceptional optical quality (up to 98 CRI, 1x2 Step MacAdam Ellipse) and supports multiple dimming protocols down to 0.1%. It offers a selection of compatible lens filters and accessories, and includes mounting options such as flush mount, surface mount, suspended, and pendant mount. The modular heatsink and power supply are removable and upgradeable. Available in standard 15-inch and shallow 12-inch heights.

LUMENS	<b>High Performance:</b> 900L, 1200L, 1500L and 2000L <b>Warm Dimming:</b> 900L, 1200L, 1500L and 2000L <b>Xicato Artist:</b> 900L, 1200L and 1500L
CCT & DYNAMIC PLATFORMS	<b>High Performance:</b> 27K, 30K, 35K, 40K and 50K <b>Warm Dimming:</b> 30K-18K, 30K-22K and 27K-18K <b>Xicato Artist:</b> 27K, 30K, 30K-VIB, 35K and 40K
CRI	<b>High Performance:</b> 90+ and 98+ <b>Warm Dimming:</b> 90+ <b>Xicato Artist:</b> 90+ and 98+
COLOR QUALITY	2 Step MacAdam Ellipse
DISTRIBUTIONS	Narrow Spot (15°), Spot (24°), Medium (36°) and Wide (60°)
DRIVER	<b>High Performance:</b> DIM10, LUTH, LUTFTB, ELDO10.1-LIN, ELDODMX.1, ELDODALI.1, DIMTR, BLE-CASAMBI, POE, DIM10-0-OFF, ELDO10-LOG, XSR and DIM10-AUX <b>Warm Dimming:</b> DIM10, LUTH, LUTFTB, ELDO10.1-LIN, ELDODMX.1, ELDODALI.1, DIMTR, BLE-CASAMBI, POE, DIM10-0-OFF, ELDO10-LOG, XSR and DIM10-AUX <b>Xicato Artist:</b> DIM10, LUTH, LUTFTB, ELDO10.1-LIN, ELDODMX.1, ELDODALI.1, DIMTR, BLE-CASAMBI, POE, DIM10-0-OFF, ELDO10-LOG, XSR and DIM10-AUX
TRIM OPTIONS	<b>Downlight:</b> Flanged, Trimless, Millwork <b>Pinhole:</b> Flanged, Trimless, Millwork
FINISH OPTIONS	<b>Anodized:</b> White (WH), Black (BK), Chrome (CL), Satin Haze (SHZ), Silver (SI), Bronze (BZ), Custom Color (RAL) <b>Diecast:</b> White (WH), Black (BK), Silver (SI), Bronze (BZ), Custom Color (RAL)
EMERGENCY	EMG-10, EMG-20, EMG-10-SDT, EMG-20-SDT and GTD
LIFETIME	LED is rated for >60,000 hours at 70% lumen maintenance
PHOTOMETRIC TESTS	In Accordance with IES LM79-08, LM80 and TM-30, TM-21



3"

BOLD-3-CYL-UWM

3" Up Down Wall Mount Architectural Cylinders

Bold Cylinders Series

High Performance: BOLD-3-CYL-UWM-900L-27K-90-15D-DIM10-120V

Series	Lumens	CCT	CRI	Optics	Driver	Voltage	Emergency	Options	Optical Accessories
<b>BOLD-3-CYL-UWM</b>	<b>900L</b>	<b>27K</b>	<b>90+</b>	<b>15D</b> Narrow Spot (15°)	<b>DIM10</b>	<b>120V</b>	-	-	-
	<b>1200L</b>	<b>30K</b>	<b>98+ <b>2</b></b>	<b>24D</b> Spot (24°)	<b>LUTH</b>	<b>MVOLT</b>	All emergency options require top access, remote emergency test switch included	<b>RIF</b> RIF Filter	<b>SOFL</b> Solite Frosted
	<b>1500L</b>	<b>35K</b>		<b>36D</b> Medium (36°)	<b>LUTFTB</b>	<b>347V <b>4</b></b>		<b>REM 5</b> Single Remote Dimming Driver	<b>SFL</b> Soft Focus Lens
	<b>2000L</b>	<b>40K</b>		<b>60D</b> Wide (60°)	<b>ELDO10.1-LIN</b>		<b>EMG-10</b>	<b>BABA</b> Made in America Compliance	<b>SPD</b> Spread Linear Lens
					<b>ELDODMX.1</b>		<b>EMG-20</b>	<b>Controls</b> See last page	<b>UVL</b> UV Lens
					<b>ELDODALI.1</b>		<b>EMG-10-SDT</b>		<b>HCL</b> Honey Comb Louver
					<b>DIMTR <b>3</b></b>		<b>EMG-20-SDT</b>		<b>PRS</b> Prismatic Lens
					<b>BLE-CASAMBI</b>		<b>GTD</b>		
					<b>POE</b>				
					<b>DIM10-0-OFF</b>				
					<b>ELDO10-LOG</b>				
					<b>XSR</b>				
					<b>DIM10-AUX</b>				

Any fixture can take maximum 2 Optical Accessories   **1** The highest lumen will not be compatible with any optical accessories   **2** 98+ CRI is available only on 27K, 30K and 40K   **3** DIMTR is only available with 120V  
**4** 347V is only available with DIM10   **5** Remote mount Maximum distance from light fixture to remote power supply is 100' using 14 gauge wire, 50' using 16 gauge wire

Warm Dimming: BOLD-3-CYL-UWM-WDM-900L-30K-18K-90-15D-DIM10-120V

Series	Lumens	CCT	CRI	Optics	Driver	Voltage	Emergency	Options	Optical Accessories
<b>BOLD-3-CYL-UWM-WDM</b>	<b>900L</b>	<b>30K-18K</b>	<b>90+</b>	<b>15D</b> Narrow Spot (15°)	<b>DIM10</b>	<b>120V</b>	-	-	-
	<b>1200L</b>	<b>30K-22K</b>		<b>24D</b> Spot (24°)	<b>LUTH</b>	<b>MVOLT</b>	All emergency options require top access, remote emergency test switch included	<b>RIF</b> RIF Filter	<b>SOFL</b> Solite Frosted
	<b>1500L</b>	<b>27K-18K</b>		<b>36D</b> Medium (36°)	<b>LUTFTB</b>	<b>347V <b>3</b></b>		<b>REM 4</b> Single Remote Dimming Driver	<b>SFL</b> Soft Focus Lens
	<b>2000L <b>1</b></b>			<b>60D</b> Wide (60°)	<b>ELDO10.1-LIN</b>		<b>EMG-10</b>	<b>SPD</b> Spread Linear Lens	<b>SPD</b> Spread Linear Lens
					<b>ELDODMX.1</b>		<b>EMG-20</b>	<b>UVL</b> UV Lens	<b>UVL</b> UV Lens
					<b>ELDODALI.1</b>		<b>EMG-10-SDT</b>	<b>HCL</b> Honey Comb Louver	<b>HCL</b> Honey Comb Louver
					<b>DIMTR <b>2</b></b>		<b>EMG-20-SDT</b>	<b>PRS</b> Prismatic Lens	<b>PRS</b> Prismatic Lens
					<b>BLE-CASAMBI</b>		<b>GTD</b>		
					<b>POE</b>				
					<b>DIM10-0-OFF</b>				
					<b>ELDO10-LOG</b>				
					<b>XSR</b>				
					<b>DIM10-AUX</b>				

Any fixture can take maximum 2 Optical Accessories   **1** The highest lumen will not be compatible with any optical accessories   **2** DIMTR is only available with 120V   **3** 347V is only available with DIM10   **4** Remote

mount Maximum distance from light fixture to remote power supply is 100' using 14 gauge wire, 50' using 16 gauge wire

3"

**BOLD-3-CYL-UWM**

3" Up Down Wall Mount Architectural Cylinders

**Bold Cylinders Series**Xicato Artist: **BOLD-3-CYL-UWM-XIA-900L-27K-90-10D-DIM10-120V**

Series	Lumens	CCT	CRI	Optics	Driver	Voltage	Emergency	Options	Optical Accessories
<b>BOLD-3-CYL-UWM-XIA</b>	<b>900L</b>	<b>27K</b>	<b>90+</b>	<b>10D</b>	<b>DIM10</b>	<b>120V</b>	-	-	-
	<b>1200L</b>	<b>30K</b>	<b>98+ <b>2</b></b>	Very Narrow Spot (10°)	<b>LUTH</b>	<b>MVOLT</b>		<b>RIF</b>	<b>SOFL</b>
	<b>1500L <b>1</b></b>	<b>30K-VIB</b>		<b>15D</b> Narrow Spot (15°)	<b>LUTFTB</b>	<b>347V <b>4</b></b>	All emergency options require top access, remote emergency test switch included	<b>REM 5</b>	<b>SFL</b> Solite Frosted
		<b>35K</b>		<b>24D</b> Spot (24°)	<b>ELDO10.1-LIN</b>		<b>EMG-10</b>	<b>SPD</b>	<b>SPD</b> Soft Focus Lens
		<b>40K</b>		<b>36D</b> Medium (36°)	<b>ELDODMX.1</b>		<b>EMG-20</b>	<b>UVL</b>	<b>UVL</b> UV Lens
				<b>60D</b> Wide (60°)	<b>ELDODALI.1</b>		<b>EMG-10-SDT</b>	<b>HCL</b>	<b>HCL</b> Honey Comb Louver
					<b>DIMTR <b>3</b></b>		<b>EMG-20-SDT</b>	<b>PRS</b>	<b>PRS</b> Prismatic Lens
					<b>BLE-CASAMBI</b>		<b>GTD</b>		
					<b>POE</b>				
					<b>DIM10-0-OFF</b>				
					<b>ELDO10-LOG</b>				
					<b>XSR</b>				
					<b>DIM10-AUX</b>				

Any fixture can take maximum 2 Optical Accessories **1** The highest lumen will not be compatible with any optical accessories **2** 95+ CRI is not available on 50K **3** DIMTR is only available with 120V **4** 347V is only available with DIM10 **5** Remote mount Maximum distance from light fixture to remote power supply is 100' using 14 gauge wire, 50' using 16 gauge wire

**3"****BOLD-3-CYL-UWM**

3" Up Down Wall Mount Architectural Cylinders

**Bold Cylinders Series****FLANGED REFLECTOR TYPE**Example: **B3R-302-A-F-WH-WH**

Trim Options	Trim Construction	Trim Flange Opt.	Reflector Finishes	Flange Finishes
 <b>B3R-302</b> Open Downlight	<b>A</b> Anodized <b>DC</b> Diecast	<b>F</b> Flanged	<b>WH</b> White <b>BK</b> Black <b>RAL</b> Custom Color (Consult Factory)	<b>WH</b> White <b>BK</b> Black <b>RAL</b> Custom Color (Consult Factory)
 <b>B3R-328</b> Solite Lens Downlight 				
 <b>B3R-314</b> Open Pinhole				
	<b>B3R-315</b> Solite Lens Pinhole 			

**1** Only available in anodized

## 3" Up Down Wall Mount Architectural Cylinders

## Bold Cylinders Series

**DESCRIPTION**

The BOLD-3-CYL-UWM A compact architectural LED cylinder available in 3" round or square apertures, offered with open, lensed, or wallwash trim options. Designed for glare-free general illumination with a modern die-cast aesthetic, it integrates seamlessly into commercial, retail, hospitality, and high-end residential spaces.

**CONSTRUCTION**

Round and square extruded aluminum cylinders with a post-painted powder-coat finish, available in standard and shallow heights. Offered in black, silver, white, or any custom RAL color.

**OPTICAL PERFORMANCE**

The optical system features an upper TIR optic for precise beam control, with an optional Solite or soft-focus lens to diffuse the source and deliver smooth, striation-free distribution. A patented lens further refines the beam angle. All optics are field-changeable and offered in a range of beam distributions.

**SUSPENSION SYSTEM**

A standard 5-inch shallow ceiling-mount canopy is provided for direct installation to 3-1/4" to 4" octagonal or square junction boxes. The pendant-mount option includes a 10 ft adjustable aircraft cable and power cord, both field-adjustable to the desired length. Consult factory for custom mounting or stem options.

**TRIM CONSTRUCTION**

With dual trim construction and an extensive library of finish options, BOLD trims empower lighting designers to achieve both technical precision and visual harmony in any space.

**Anodized Aluminum:** Designed for visual comfort, anodized trims recess the light source to achieve a 35-degree cutoff, enhancing glare control and supporting quiet ceilings in high-performance architectural environments. The electrochemical finish ensures long-term reflectance and material integrity.

**Die-Cast:** Die-cast trims provide sharp detailing, precise fit, and the ability to seamlessly blend into the ceiling plane with high-quality painted finishes. Ideal for minimalist spaces where integration and consistency are key

**DLWNTLGHTR TRIM**

High-quality die-cast bevel trims feature a smooth, low-glare powder-coat finish and are available in open or lensed downlight, as well as lensed wall-wash options. Finishes include WT (Wheat), W (White), BK (Black), and BZ (Antique Bronze).

**THERMAL MANAGEMENT SYSTEM**

Passive-cooling die-cast aluminum heat sink dissipates heat from the LED module, supporting optimal performance and extending component life.

**OPTICAL FILTER & ACCESSORIES**

Additional lens accessories—including Frosted, Soft Focus, Spread, Honeycomb, Linear, and Solite—help meet specific design and performance requirements. Up to two accessories may be used per luminaire, and they are intended only for open, non-lensed downlight trims.

**OPERATING TEMPERATURE**

Luminaire must be installed and operated in damp or dry locations with an ambient temperature range of -4°F to 104°F (-20°C to 40°C).

**MOUNTING**

Offered in cable, stem, and surface mounting options. Cable and pendant mounts are supplied with a complete canopy assembly matched to the housing finish, and cable height can be field-adjusted up to 10 ft.

**EMERGENCY OPTIONS/CONTROLS**

The remote test switch is included. The external battery operates LED loads of up to 1000 lumens (EMG-SDTLED-10W) or up to 2000 lumens (EMG-LED-20W).

**DIM TO WARM OPTION**

Dims to Warm simulates traditional incandescent halogen lighting through dimming. When the luminaire dims to warm from 100% to .1%, it makes a smooth transition across the black body radiator while maintaining a constant CRI of 90+. Available in 30K-18K, 30K-22K or 27K-18K range.

**XICATO ARTIST SERIES LED MODULE (XIA)**

Powered by Xicato Artist Series®, which are tested to IES TM-30-15, with a color fidelity score (Rf) of 96 and a color gamut score (Rg) of 102, and color shift less than  $du'v'$  of 0.003. Featuring cold phosphor technology, improving thermal management enhancing color consistency and delaying lumen depreciation.

**NATURAL SPECTRUM (NSL)**

Natural Spectrum LED option is designed for Human Centric lighting application. Natural Spectrum LEDs diminish blue light peak, similar spectral curve to sunlight, accurate rendering of colors and reduced scattered reflection and glare.

**DIMMING & DRIVER INFORMATION**

**DIM10** - 0-10V dimming on either MVOLT 120, 277 or 347V. Dimmable down to 1% of initial lumens, standard

**LUTH** - Lutron LDE1 Hi-Lume Eco System with Soft Fade to Black 1% dimming

**LUTFTB** - Lutron PEQ0 Hi-Lume Premier Eco System LED Driver with soft-on fade to black 0.1% dimming

**ELDO10.1-LIN** - ELDO 10-Linear with linear dimming curve.

**ELDODMX.1** - EldoLED PowerDrive dimming down to 0.1%. Please see EldoLED website for wiring diagrams and a list of compatible DMX and DALI control systems.

**ELDODALI.1** - EldoLED SoloDrive DALI-2. Dimming down to 0.1%

**DIMTR** - Triac & Electronic low voltage forward phase dimming. Available in 120V only

**BLE-CASAMBI** - Luminaires may be controlled, grouped, scheduled or placed in scenes, and or zones via Casambi Bluetooth 4.0 App.

**POE** - Power-over-Ethernet Depending on the PoE manufacturer selected

**DIM10-0-OFF** - Program DIM10-to OFF with linear dimming curve 0.1%

**ELDO10-LOG** - ELDO 10-LOG with logarithmic dimming curve.

**XSR** - Xitanium SR Dimming

**DIM10-AUX** - 0-10V with Auxiliary power

**DIMTR** - Triac & Electronic low voltage forward phase dimming. Available in 120V only

# 3"

# BOLD-3-CYL-UWM

## 3" Up Down Wall Mount Architectural Cylinders

## Bold Cylinders Series

### WARRANTY

Five-year warranty for parts and components. (Labor not included)

### LISTINGS

- c-UL-us: Listed for Wet Location when used with wet-location rated trims
- c-UL-us: Listed for Feed-Through Wiring
- Energy Star and California Title 24 compliant (JA8)
- Optional Black color trim is not Energy Star certified and will not meet the requirements
- 22K and 27K are not Energy Star listed and will not meet the requirements
- BABA Compliant for government procurement under FAR, DFARS, and DOT regulations.

**3"**

**BOLD-3-CYL-UWM**

3" Up Down Wall Mount Architectural Cylinders

**Bold Cylinders** Series



WWW.EPL.COM | 718.685.0700 | LOS ANGELES

2025/11/26 15:49 @Ai™

## BOLD-3-CYL-UWM-2000L-40K-90-15D-DIM10-MVOLT-B3R-318-A-F-CL-WH

TEST NO EPL02242531

INPUT WATTS: 22.8


LUMENS: 2105

EFFICACY: 92

BEAM ANGLE: 15

SPACING CRITERIA: 0.32

## CANDELA DISTRIBUTION



## CANDELA TABLE

0°	0° 90°		0.00° 90.00°		ZONE	LUMENS	
	11382	11393	974957	975861			
10°	5042	6312	45.00°	5204	5789	10° - 20°	778
20°	1037	1320	55.00°	1201	1419	20° - 30°	317
30°	297	383	65.00°	30	28	30° - 40°	125
40°	90	110	75.00°	23	23	40° - 50°	41
50°	21	24	85.00°	39	39	50° - 60°	10
60°	2	2				60° - 70°	1
70°	0	0				70° - 80°	0
80°	0	0				80° - 90°	0
90°	0	0					

## ZONAL LUMEN SUMMARY

ZONE	UMENS	% LUMINAIRE
0° - 20°	1610	76%
0° - 30°	1926	92%
0° - 40°	2051	97%
0° - 60°	2102	100%
0° - 80°	2103	100%
0° - 90°	2103	100%

## CONE OF LIGHT

## INDOOR COEFFICIENTS OF UTILIZATION

MOUNTING HEIGHT	FC AT BEAM CENTER	BEAM DIA. 0°	BEAM DIA. 90°	pf				pc				pw									
				80%		70%		50%		30%		20%		10%							
6.0 ft	316.2 fc	2.2 ft	2.2 ft	120	120	118	118	118	118	112	112	112	108	108	103	103	103	101			
8.0 ft	177.8 fc	3.0 ft	3.0 ft	116	114	112	110	114	112	110	109	108	107	105	104	103	102	101	99	98	
10.0 ft	113.8 fc	3.7 ft	3.7 ft	109	104	100	97	107	103	99	97	100	97	95	98	99	98	97	96	94	
12.0 ft	79.0 fc	4.4 ft	4.4 ft	105	100	96	93	104	99	95	92	97	94	91	95	92	90	93	91	89	88
14.0 ft	58.1 fc	5.2 ft	5.2 ft	102	96	92	89	101	95	91	89	94	90	88	92	89	87	91	88	86	85
16.0 ft	44.5 fc	5.9 ft	5.9 ft	99	93	89	86	98	92	88	85	91	87	85	90	87	84	88	86	84	83
18.0 ft	35.1 fc	6.6 ft	6.6 ft	96	90	86	83	95	89	85	82	88	85	82	87	84	82	86	83	81	80
20.0 ft	28.5 fc	7.4 ft	7.4 ft	94	87	83	80	93	87	83	80	86	82	80	85	82	79	84	81	79	78
				91	85	80	78	90	84	80	78	83	80	77	83	79	77	82	79	77	76
				89	82	78	76	88	82	78	75	81	78	75	81	77	75	80	77	75	74

## INDOOR COEFFICIENTS OF UTILIZATION

ZONE	20%				10%				0%			
	70%	50%	30%	10%	70%	50%	30%	10%	70%	50%	30%	10%
0° - 20°	1610	108	103	103	108	107	108	103	102	101	100	99
0° - 30°	1926	105	104	104	108	107	105	104	103	102	101	99
0° - 40°	2051	102	101	101	104	102	104	100	101	101	100	98
0° - 60°	2102	99	98	98	104	102	104	101	101	101	100	97
0° - 80°	2103	97	96	96	104	102	104	101	101	101	100	95
0° - 90°	2103	95	94	94	104	102	104	101	101	101	100	93

## BOLD-3-CYL-UWM-2000L-40K-90-26D-DIM10-MVOLT-B3R-318-A-F-CL-WH

TEST NO EPL02242531

INPUT WATTS: 22.8


LUMENS: 2189

EFFICACY: 96

BEAM ANGLE: 24

SPACING CRITERIA: 0.41

## CANDELA DISTRIBUTION



## CANDELA TABLE

0°	0° 90°		0.00° 90.00°		ZONE	LUMENS
	9156	9205	784230	788471		
10°	5800	6438	45.00°	5518	6902	746
20°	1275	1604	55.00°	1213	1846	937
30°	290	357	65.00°	28	73	326
40°	94	118	75.00°	23	26	120
50°	23	30	85.00°	39	39	46
60°	1	3				12
70°	0	0				1
80°	0	0				0
90°	0	0				0

## ZONAL LUMEN SUMMARY

ZONE	UMENS	% LUMINAIRE
0° - 20°	1683	77%
0° - 30°	2009	92%
0° - 40°	2129	97%
0° - 60°	2186	100%
0° - 80°	2187	100%
0° - 90°	2187	100%

## CONE OF LIGHT

## INDOOR COEFFICIENTS OF UTILIZATION

MOUNTING HEIGHT	FC AT BEAM CENTER	BEAM DIA. 0°	BEAM DIA. 90°	pf				pc				pw									
				80%		70%		50%		30%		20%		10%							
6.0 ft	254.3 fc	2.8 ft	2.8 ft	120	120	117	117	117	117	112	112	112	107	107	103	103	101	101			
8.0 ft	143.1 fc	3.7 ft	3.7 ft	116	114	112	110	113	111	110	108	107	106	105	104	103	102	100	99	99	97
10.0 ft	91.6 fc	4.6 ft	4.6 ft	108	105	102	100	106	104	101	103	101	99	98	97	96	95	93	95	93	90
12.0 ft	63.6 fc	5.5 ft	5.5 ft	105	99	95	92	103	98	94	91	96	93	90	94	91	89	92	90	87	86
14.0 ft	46.7 fc	6.5 ft	6.5 ft	101	95	91	88	100	94	90	87	93	89	87	91	88	86	90	87	85	84
16.0 ft	35.8 fc	7.4 ft	7.4 ft	98	87	84	81	97	91	87	84	90	86	83	85	85	83	87	84	82	81
18.0 ft	28.3 fc	8.3 ft	8.3 ft	95	89	84	81	94	88	84	81	87	83	81	86	83	80	85	82	80	79
20.0 ft	22.9 fc	9.2 ft	9.2 ft	92	86	81	78	92	85	81	78	84	81	78	83	80	78	82	80	77	76
				90	83	79	76	89	83	79	76	82	78	76	81	78	75	80	77	75	74
				88	81	76	74	87	80	76	74	80	76	73	79	76	73	78	75	73	72

## INDOOR COEFFICIENTS OF UTILIZATION


ZONE	20%				10%				0%			
	70%	50%	30%	10%	70%	50%	30%	10%	70%	50%	30%	10%
0° - 20°	1683	108	103	10								

## BOLD-3-CYL-UWM-2000L-40K-90-36D-DIM10-MVOLT-B3R-318-A-F-CL-WH

TEST NOEPL02242531

INPUT WATTS: 21.7 LUMENS: 2364 EFFICACY: 109 BEAM ANGLE: 36 SPACING CRITERIA: 0.61

## CANDELA DISTRIBUTION



## CANDELA TABLE

	0°	90°		0.00°	90.00°
0°	4880	4891		743047	744724
10°	4020	4203		17394	18484
20°	2302	2549		5289	5575
30°	724	876		126	256
40°	166	182		53	59
50°	42	45		87	87
60°	7	7			
70°	0	0			
80°	0	0			
90°	0	0			

## LUMINANCE (cd/sq.m)

	0°	90°		0.00°	90.00°
0°	4880	4891		743047	744724
10°	4020	4203		17394	18484
20°	2302	2549		5289	5575
30°	724	876		126	256
40°	166	182		53	59
50°	42	45		87	87
60°	7	7			
70°	0	0			
80°	0	0			
90°	0	0			

## LUMENS PER ZONE

ZONE	LUMENS
0° - 10°	446
10° - 20°	885
20° - 30°	689
30° - 40°	250
40° - 50°	71
50° - 60°	20
60° - 70°	2
70° - 80°	0
80° - 90°	0

## ZONAL LUMEN SUMMARY

ZONE	UMENS	% LUMINAIRE
0° - 20°	1330	56%
0° - 30°	2019	85%
0° - 40°	2268	96%
0° - 60°	2360	100%
0° - 80°	2362	100%
0° - 90°	2362	100%

## CONE OF LIGHT

MOUNTING HEIGHT	FC AT BEAM CENTER	BEAM DIA. 0°	BEAM DIA. 90°	pf								80%				20%
				80%				20%				80%				0%
pw	70%	50%	30%	10%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	0%
6.0 ft	135.5 fc	4.3 ft	4.3 ft													
8.0 ft	76.2 fc	5.7 ft	5.8 ft													
10.0 ft	48.8 fc	7.2 ft	7.2 ft													
12.0 ft	33.9 fc	8.6 ft	8.7 ft													
14.0 ft	24.9 fc	10.0 ft	10.1 ft													
16.0 ft	19.1 fc	11.4 ft	11.6 ft													
18.0 ft	15.1 fc	12.9 ft	13.0 ft													
20.0 ft	12.2 fc	14.3 ft	14.4 ft													

## INDOOR COEFFICIENTS OF UTILIZATION


	20%								0%							
pf	70%	50%	30%	10%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%	0%
0	119	119	119	119	117	117	117	117	111	111	111	111	107	107	102	102
1	115	112	110	108	112	110	108	106	104	103	102	101	99	98	97	95
2	110	105	102	99	108	104	101	98	96	98	96	94	95	93	92	90
3	105	100	95	92	103	98	94	91	96	92	90	93	91	88	89	87
4	101	94	89	86	99	93	89	85	91	87	84	89	86	83	85	82
5	97	89	84	81	95	89	84	80	87	83	80	85	82	79	84	81
6	93	85	80	76	91	84	79	76	83	79	75	82	78	75	80	77
7	89	81	76	72	88	80	76	72	79	75	72	78	74	71	77	74
8	86	77	72	69	85	77	72	69	76	71	68	75	71	68	74	68
9	82	74	69	65	81	74	69	65	73	68	65	72	68	65	71	67
10	79	71	66	63	78	71	66	62	70	65	62	69	65	62	68	65

## BOLD-3-CYL-UWM-2000L-40K-90-60D-DIM10-MVOLT-B3R-318-A-F-CL-WH

TEST NOEPL02242531

INPUT WATTS: 21.7 LUMENS: 2264 EFFICACY: 104 BEAM ANGLE: 60 SPACING CRITERIA: 0.80

## CANDELA DISTRIBUTION



## CANDELA TABLE

	0°	90°		0.00°	90.00°
0°	2907	2908		442703	442843
10°	2630	2718		451822	26949
20°	1971	2097		554407	4030
30°	1123	1242		65133	76
40°	290	368		7559	53
50°	36	38		8587	70
60°	7	5			
70°	0	0			
80°	0	0			
90°	0	0			

## LUMINANCE (cd/sq.m)

	0°	90°		0.00°	90.00°
0°	2907	2908		442703	442843
10°	2630	2718		451822	26949
20°	1971	2097		554407	4030
30°	1123	1242		65133	76
40°	290	368		7559	53
50°	36	38		8587	70
60°	7	5			
70°	0	0			
80°	0	0			
90°	0	0			

## LUMENS PER ZONE

ZONE	LUMENS
0° - 10°	281
10° - 20°	657
20° - 30°	731
30° - 40°	459
40° - 50°	114
50° - 60°	17
60° - 70°	2
70° - 80°	0
80° - 90°	0

## ZONAL LUMEN SUMMARY

ZONE	UMENS	% LUMINAIRE
0° - 20°	938	41%
0° - 30°	1669	74%
0° - 40°	2128	94%
0° - 60°	2259	100%
0° - 80°	2262	100%
0° - 90°	2262	100%

## CONE OF LIGHT

MOUNTING HEIGHT	FC AT BEAM CENTER	BEAM DIA. 0°	BEAM DIA. 90°	pf								80%				20%
				80%				20%				80%				0%
pw	70%	50%	30%	10%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	0%
6.0 ft	80.8 fc	6.1 ft	6.1 ft													
8.0 ft	45.4 fc	8.1 ft	8.1 ft													
10.0 ft	29.1 fc	10.2 ft	10.2 ft													
12.0 ft	20.2 fc	12.2 ft	12.2 ft													
14.0 ft	14.8 fc	14.2 ft	14													

BRAND	LUTRON	enlighted	LEVITON	ENCELLIUM	PHILIPS	legrand	NA LIGHTING CONTROLS		
CONTROL UNIT	<input type="checkbox"/> <b>FCJS-010</b> Lutron Vive 0-10V Individual Pow Pak (Luminaire is shipped Vive Enabled) <b>14</b> <input type="checkbox"/> <b>FCJS-ECO</b> Lutron Vive Eco-system Pow Pak (Luminaire is shipped Vive Enabled) <input type="checkbox"/> <b>A-WN-D01-RF-WH</b> Athena wireless node (RF only) (White) <input type="checkbox"/> <b>A-WN-D01-OCC-WH</b> Athena wireless node with sensor (White)		<input type="checkbox"/> <b>CU-4E-FMH</b> Fixture Mount Control Unit <b>15</b>	<input type="checkbox"/> <b>ZL027-NOW</b> Intellect Power Control Module <b>16</b>  <input type="checkbox"/> <b>ZL027-DLE</b> Intellect Power Control Module <b>16</b>	<input type="checkbox"/> <b>EN-WCM2-ZB-DR</b> Wireless Control Module <b>17</b>  <input type="checkbox"/> <b>ENA-LC-ZB-BK-DR</b> Wireless Area Lighting Control Module <b>17</b>		<input type="checkbox"/> <b>LMFC-011</b> ON/OFF/0-10V dimming fixture controller <b>19</b>  <input type="checkbox"/> <b>FS-PP-V2 FS-PP</b> Fixture Integrated Sensor Power Pack <b>19</b>  <input type="checkbox"/> <b>LMFS-601</b> Integrated Fixture Sensor & Controller		
INTEGRATED OCCUPANCY & DAYLIGHT SENSOR	<input type="checkbox"/> <b>DFCSJ-OEM-OCC</b> Clear Connect (RF) and Occupancy/Daylight Sensing <b>2</b>		<input type="checkbox"/> <b>SU-5E-IOT</b> IoT Node Micro Sensor <input type="checkbox"/> <b>SU-5E-CL</b> Connected Micro Sensor <input type="checkbox"/> <b>SU-5E-IL</b> Indipendent Micro Sensor <input type="checkbox"/> <b>SU-5S-H(IoT/CL/IL)</b> Serface Mount Sensor <b>2</b>  Must be Specified with CU-4E-FMH Control Unit	<input type="checkbox"/> <b>ZL00J-TOW</b> Intellect Intelligent Fixture Control System <b>2</b>  <input type="checkbox"/> <b>ZL00J-DOW</b> Intellect Intelligent Fixture Control System <b>2</b>	<input type="checkbox"/> <b>EN-CLM-PIR-DD-ZB</b> SensiLUM™ Wireless Integrated Sensor  <input type="checkbox"/> <b>ZBHACLM-DIM-ENC</b> Connected Lighting Module DIM <b>2</b>	<input type="checkbox"/> <b>SNS 212</b> EasyAir Daylight and Occupancy sensor  <input type="checkbox"/> <b>SNS300</b> SNS300 for networks <b>2</b>	<input type="checkbox"/> <b>FD-301</b> Fixture integrated Daylight Dimming Sensor <b>2</b>  <input type="checkbox"/> <b>FS-205</b> Fixture integrated passive infrared occupancy sensor <b>2</b>	<input type="checkbox"/> <b>NXRM</b> HubbNETTM Radio Module  <input type="checkbox"/> <b>NXSMP2-OMNI</b> Integrated Fixture Sensor & Controller  <input type="checkbox"/> <b>NXSMP2-SMI</b> NX Slide Mount Indoor Sensor Module	
* WIRELESS OCCUPANCY SENSOR	<input type="checkbox"/> <b>LRF2-OCR2B-P-WH</b> Ceiling mount360°, occupancy/vacancy sensor <b>3</b>	N/A	N/A	N/A	<input type="checkbox"/> <b>EN-SCPPH-1500-ZB</b> Wireless Passive Infrared Occupancy and Photo Sensors <b>3</b>	N/A	<input type="checkbox"/> <b>LMDC-100</b> Dual technology PIR Ceiling Mount Occupancy Sensor <b>3</b>	<input type="checkbox"/> <b>NXSMP2-SMI</b> NX Slide Mount Indoor Sensor Module	
* WIRELESS DAYLIGHT SENSOR	<input type="checkbox"/> <b>LRF2-DCRB-WH</b> Ceiling-mount daylight sensor <b>3</b>	N/A	N/A	N/A	<input type="checkbox"/> <b>EN-SCPPH-1500-ZB</b> Wireless Passive Infrared Occupancy and Photo Sensors <b>3</b>	N/A	<input type="checkbox"/> <b>LMLS-400</b> Single zone switching and dimming digital photosensor <b>3</b>	<input type="checkbox"/> <b>LUXSTATS</b> Luxstat Light Sensor for Luxstat Control Modules, 3 to 6000 FC	
* WIRELESS OCCUPANCY & DAYLIGHT SENSOR		N/A		<input type="checkbox"/> <b>SU-5E-IOT</b> IoT Node Micro Sensor <input type="checkbox"/> <b>SU-5E-CL</b> Connected Micro Sensor <input type="checkbox"/> <b>SU-5E-IL</b> Indipendent Micro Sensor <input type="checkbox"/> <b>SU-5S-H (IoT/CL/IL)</b> Serface Mount Sensor <b>3</b>  Must be specified with CU-4E-FMH Control Unit	<input type="checkbox"/> <b>ZL00J-TOW</b> Intellect Intelligent Fixture Control System  <input type="checkbox"/> <b>ZL00J-DOW</b> Intellect Intelligent Fixture Control System <b>3</b>	<input type="checkbox"/> <b>EN-CLMPIR-DD-ZB</b> SensiLUM™ Wireless Integrated Sensor  <input type="checkbox"/> <b>ZBHACLM-DIM-ENC</b> Connected Lighting Module DIM <b>3</b>	<input type="checkbox"/> <b>SNS212-CMP</b> SNS-212 for Grouping <b>3</b>	N/A	<input type="checkbox"/> <b>NXSMDT</b> Indoor Ceiling Mount Sensor - OMNI
ACCESSORIES		N/A		<input type="checkbox"/> <b>TMC-SU-5E</b> Tile Mount Carrier <input type="checkbox"/> <b>CBL-5E-CU4-30N</b> 30 inch Sensor cable for CU-4 and IoT Ready <input type="checkbox"/> <b>CBL-5E-CU4-7F</b> 7 Foot sensor cable for CU-4 and IoT Ready Driver	N/A	N/A	N/A	N/A	

1- Luminaire will be shipped with Powerpacks pre-installed, ready to be integrated to designated control systems

2- Luminaire will be shipped with Sensors installed on the luminaire, allowing for individual luminaire control. Luminaires will be ready to be integrated with designated control systems

3- Luminaire will be shipped with Sensors to be remotely installed on the ceiling. Luminaires will be ready to be integrated with designated control systems

4- Luminaire will be compatible with LUTRON LRF2-OCR2B-PWH Ceiling mount 360deg occupancy/vacancy sensor & LRF2-DCRB-WH ceiling mount daylight sensor Sensors must be ordered through Lutron

5- Luminaire will be compatible with ENLIGHTED SU-5E-IOT, SU-5E-CL, SU-5E-IL, SU-5S-H, Sensors

6- Luminaire will be compatible with LEVITON Intellect APP & Keypad room controller

7- Luminaire will be compatible with EN-SCPPH-1500-ZB Wireless passive infrared occupancy and photo sensor

8- Luminaire will be compatible with philips field and wireless switch

9- Luminaire will be compatible with DLM Room control system LMPB-100. Sensors must be ordered through Legrand.