

ADJ.  
SPOT-  
LIGHT



### FREE SERIES MODULE FEATURES

**Compact Dimensions:**

Diameter 1 3/4" x Height 3 15/16", ideal for discreet installation

**High Efficiency:**

Consumes only 5W of power while providing 235LM of light output

**Adjustable Beam Spread:**

Zoomable beam angle from 12° to 50° for focused or broader illumination

**Advanced Dimming and Controls:**

Compatible with Non-dimming, DALI, CASAMBI, and 0-10V systems for versatile control

**Durable Finish:**

Black coating with an IP20 rating, suitable for indoor environments

**Easy Installation:**

Designed for track mounting, ensuring a hassle-free setup

### TRACK MODULE ORDERING GUIDE

Basic Unit	Beam Angle	Driver	Voltage	Lumens	CCT	CRI	Finish
<b>FR-102</b> 1-3/4" Adjustable Spotlight	<b>ADJ</b> 12° - 50° Distribution	<b>DIM10</b> 0-10V Dimming	<b>48</b> 48VDC	<b>235L</b> 235 lumens	<b>27K</b> 2700K	<b>90</b>	<b>BK</b> Black Finish, Black Housing
		<b>BLE-CASAMBI</b> Bluetooth Low Energy Casambi			<b>30K</b> 3000K		
		<b>DALI-2</b>			<b>35K</b> 3500K		
		<b>TUY</b> TUYA			<b>40K</b> 4000K		

### DESCRIPTION

The Free Series Track-Mounted Zoomable Spotlight combines sleek design with exceptional performance, offering versatile lighting solutions with adjustable beam spreads. Perfect for precise indoor lighting applications, it ensures vibrant and accurate color rendering with multiple CCT options.

### SPECIFICATIONS DATA

Lumens	235
Size(s)	Ø 1-3/4" x 3-15/16" L
Finish(es)	Black
Driver(s)	0-10V, DALI-2, Tuya, CASAMBI
Input Voltage	48V
Beam Angle	12° - 50°
CRI	>90
CCT	27K, 30K, 35K, 40K
Power (W)	5

PIVOT



TILT



