



LINEAR

FREE SERIES MODULE FEATURES

Compact Dimensions:

Length 12" / 24" / 36" x Width 7/8" x Height 1 5/8", ideal for discreet installation

High Efficiency:

Consumes 7W / 14W / 20W of power while providing 980LM / 1960LM / 2800LM of light output

Wide Beam Angle:

100° beam angle for broad and even illumination

Advanced Dimming and Controls:

Compatible with Non-dimming, DALI, CASAMBI, and 0-10V systems for versatile control

Durable Finish:

Black coating with an IP20 rating, suitable for indoor environments

Easy Installation:

Designed for track mounting, ensuring a hassle-free setup

TRACK MODULE ORDERING GUIDE

Basic Unit	Beam Angle	Driver	Voltage	Lumens	CCT	CRI	Finish
FR-203-1 12" Linear w/ Microprismatic	PR 65° x 90° Distribution	DIM10 0-10V Dimming	48 48VDC	2800L 2800 lumens	27K 2700K	90	BK Black Finish, Black Housing
FR-203-2 24" Linear w/ Microprismatic		BLE-CASAMBI Bluetooth Low Energy Casambi		1960L 1960 lumens	30K 3000K		
FR-203-3 36" Linear w/ Microprismatic		DALI-2		980 980 lumens	35K 3500K		
		TUY TUYA			40K 4000K		

DESCRIPTION

The Free Series Track-Mounted LED Linear Module combines sleek design with high performance, perfect for versatile indoor lighting applications. With high CRI and multiple CCT options, it ensures vibrant and accurate color rendering with a wide beam angle for even illumination.

SPECIFICATIONS DATA

Lens	Microprismatic
Lumens	2800 / 1960 / 980
Size(s)	7/8" x 1-5/8" x 12, 24, 36"
Finish(es)	Black
Driver(s)	0-10V, DALI-2, Tuya, CASAMBI
Input Voltage	48V
Beam Angle	100°
CRI	>90
CCT	27K, 30K, 35K, 40K
Power (W)	20 / 14 / 7





