

SPOT-LIGHT



FREE SERIES MODULE FEATURES

Compact Dimensions:

Diameter 2 1/16" x Height 3 3/4", ideal for discreet installation

High Efficiency:

Consumes only 10W of power while providing 770LM / 830LM of light output

Adjustable Beam Angles:

Available in 24° and 36° options to provide targeted or broader illumination

Advanced Dimming and Controls:

Compatible with Non-dimming, DALI, CASAMBI, and 0-10V systems for versatile control

Durable Finish:

Black coating with an IP20 rating, suitable for indoor environments

Easy Installation:

Designed for track mounting, ensuring a hassle-free setup

TRACK MODULE ORDERING GUIDE

Basic Unit	Beam Angle	Driver	Voltage	Lumens	CCT	CRI	Finish
FR-301 2-1/16" Spotlight	24D 24° Distribution	DIM10 0-10V Dimming	48 48VDC	830L 830 lumens	27K 2700K	90	BK Black Finish, Black Housing
	36D 36° Distribution	BLE-CASAMBI Bluetooth Low Energy Casambi		770L 770 lumens	30K 3000K		
		DALI-2			35K 3500K		
		TUY TUYA			40K 4000K		

DESCRIPTION

The Free Series Track-Mounted LED Spotlight Luminaire combines sleek design with exceptional performance, ideal for versatile indoor lighting applications. With high CRI and multiple CCT options, it ensures vibrant and accurate color rendering with adjustable beam angles.

SPECIFICATIONS DATA

Lumens	830 / 770
Size(s)	Ø 2-1/16" x 3-3/4" L
Finish(es)	Black
Driver(s)	0-10V, DALI-2, Tuya, CASAMBI
Input Voltage	48V
Beam Angle	24°, 36°
CRI	>90
CCT	27K, 30K, 35K, 40K
Power (W)	10

PIVOT



TILT



