





FREE SERIES MODULE FEATURES

Compact Dimensions:

Diameter 2 9/16" x Height 5 5/16", ideal for discreet installation

High Efficiency:

Consumes only 12W of power while providing 660LM of light output

Adjustable Beam Spread:

Zoomable beam angle from 15° to 36° for focused or broader illumination

Advanced Dimming and Controls:

Compatible with Non-dimming, DALI, CASAMBI, and 0-10V systems for versatile control

Durable Finish:

Black coating with an IP20 rating, suitable for indoor environments

Easy Installation:

Designed for track mounting, ensuring a hassle-free setup

TRACK MODULE ORDERING GUIDE

DESCRIPTION

The Free Series Track-Mounted Zoomable Spotlight combines sleek design with exceptional performance, offering versatile lighting solutions with adjustable beam spreads. Perfect for precise indoor lighting applications, it ensures vibrant and accurate color rendering with multiple CCT options.

SPECIFICATIONS DATA

Lumens	660		
Size(s)	Ø 2-9/16" x 5-5/16" L		
Finish(es)	Black 0-10V, DALI-2, Tuya, CASAMBI		
Driver(s)			
Input Voltage	48V		
Beam Angle	15° - 36°		
CRI	>90		
ССТ	27K, 30K, 35K, 40K		
Power (W)	12		

PIVOT





Basic Unit	Beam Angle	Driver	Voltage	Lumens	ССТ	CRI	Finish
FR-302 2-9/16" Adjustable Spotlight	ADJ 15° - 36° Distribution	DIM10 0-10V Dimming		660 lumens	27K 2700K	90	BK Black Finish, Black Housing
		BLE-CASAMBI Bluetooth Low Energy Casambi			30K 3000K		
		DALI-2			35K 3500K		
		TUY			40K 4000K		



Free Series

FR-302







