

SPOT-LIGHT



FREE SERIES MODULE FEATURES

Compact Dimensions:

Diameter 2 7/16" x Height 5 11/16", ideal for discreet design

High Efficiency:

Consumes only 15W of power while providing 800LM / 865LM / 850LM of light output

Adjustable Beam Angles:

Available in 24° and 36° options to provide targeted or broader illumination

Advanced Dimming and Controls:

Compatible with Non-dimming, DALI, CASAMBI, and 0-10V systems for versatile control

Durable Finish:

Black coating with an IP20 rating, suitable for indoor environments

Easy Installation:

Designed for track mounting, ensuring a hassle-free setup

TRACK MODULE ORDERING GUIDE

Basic Unit	Beam Angle	Driver	Voltage	Lumens	CCT	CRI	Finish
FR-401 2-7/16" Spotlight	24D 24° Distribution	DIM10 0-10V Dimming	48 48VDC	865L 865 lumens	27K 2700K	90	BK Black Finish, Black Housing
	36D 36° Distribution	BLE-CASAMBI Bluetooth Low Energy Casambi		850L 850 lumens	30K 3000K		
		DALI-2		800L 800 lumens	35K 3500K		
		TUY TUYA		40K 4000K			

DESCRIPTION

The Free Series Track-Mounted LED Spotlight Luminaire combines sleek design with exceptional performance, ideal for versatile indoor lighting applications. With high CRI and multiple CCT options, it ensures vibrant and accurate color rendering with adjustable beam angles.

SPECIFICATIONS DATA

Lumens	865 / 850 / 800
Size(s)	Ø 2-7/16" x 5-11/16" L
Finish(es)	Black
Driver(s)	0-10V, DALI-2, Tuya, CASAMBI
Input Voltage	48V
Beam Angle	24°, 36°
CRI	>90
CCT	27K, 30K, 35K, 40K
Power (W)	15

PIVOT



TILT



