



LINEAR

FREE SERIES MODULE FEATURES

Compact Dimensions:

Length 12" / 24" / 36" x Width 7/8" x Height 1 5/8", ideal for discreet installation

High Efficiency:

Consumes 7W / 14W / 20W of power while providing 700LM / 1400LM / 2000LM of light output

Lens Diffuser with Batwing Distribution:

Offers a wide, even spread of light, reducing glare and providing uniform illumination with beam angles of 100° x 90° x 15°

Advanced Dimming and Controls:

Compatible with Non-dimming, DALI, CASAMBI, and 0-10V systems for versatile control

Durable Finish:

Black coating with an IP20 rating, suitable for indoor environments

TRACK MODULE ORDERING GUIDE

Basic Unit	Beam Angle	Driver	Voltage	Lumens	CCT	CRI	Finish
FR-403-1 12" Linear w/ Batwing Lens	BW 100° x 90° x 15° Distribution	DIM10 0-10V Dimming	48 48VDC	2000L 2000 lumens	27K 2700K	90	BK Black Finish, Black Housing
FR-403-2 24" Linear w/ Batwing Lens		BLE-CASAMBI Bluetooth Low Energy Casambi		1400L 1400 lumens	30K 3000K		
FR-403-3 36" Linear w/ Batwing Lens		DALI-2		700 700 lumens	35K 3500K		
		TUY TUYA			40K 4000K		

DESCRIPTION

The Free Series Track-Mounted LED Linear Module combines sleek design with high performance, perfect for versatile indoor lighting applications. With high CRI and multiple CCT options, it ensures vibrant and accurate color rendering with a wide beam angle for even illumination.

SPECIFICATIONS DATA

Lens	Batwing
Lumens	2000 / 1400 / 700
Size(s)	7/8" x 1-5/8" x 12, 24, 36"
Finish(es)	Black
Driver(s)	0-10V, DALI-2, Tuya, CASAMBI
Input Voltage	48V
Beam Angle	100° x 90° x 15°
CRI	>90
CCT	27K, 30K, 35K, 40K
Power (W)	20 / 14 / 7





