



FREEPOINT FEATURES

Slim Profile Design

7/8" W x 7/8" H, available in lengths of 24", 35", and 47"

High Luminous Flux

Produces 900 lumens (24"), 1350 lumens (35"), and 1800 lumens (47") with an efficacy of 75 LM/W

Superior Color Rendering

90+ CRI for vibrant and accurate color representation

Flexible Color Temperatures

Available in 2700K, 3000K, 3500K, and 4000K

Advanced Dimming Control

Supports 0-10V, DALI-2, TUYA, and CASAMBI systems

Wide Beam Angle

110° for broad and even light distribution

Glare-Free Lighting

Low UGR for comfortable and effective illumination

TRACK MODULE ORDERING GUIDE

Basic Unit	Beam Angle	Driver	Voltage	Lumens	CCT	CRI	Finish
FRM-103-2 24" Linear with Frosted Diffuser	110D 110° Distribution	DIM10 0-10V Dimming	48 48VDC	450L 450 lumens per foot	27K 2700K	90	BK Black Finish, Black Housing
FRM-103-3 36" Linear with Frosted Diffuser		BLE-CASAMBI Bluetooth Low Energy Casambi			30K 3000K		
FRM-103-4 48" Linear with Frosted Diffuser		DALI-2			35K 3500K		
		TUY TUYA			40K 4000K		

DESCRIPTION

The Single-Hole Linear Module with Frosted Diffuser Lens is a versatile and efficient lighting solution. Available in lengths of 24", 36", and 48", it delivers up to 1800 lumens with a CRI of 90+ and a 110° beam angle. Choose from various color temperatures and dimming options, all in a sleek black finish.

SPECIFICATIONS DATA

Lumens	450 LM/ft
Size(s)	7/8" W x 24"/36"/48" L
Efficacy	75 LM/W
Finish(es)	Black
Driver(s)	0-10V, DALI-2, Tuya, CASAMBI
Input Voltage	48V
Beam Angle	110°
UGR	<10
CRI	>90
CCT	27K, 30K, 35K, 40K
Power (W)	6 W/ft

