



FREEPOINT FEATURES

Slim Profile Design

1 1/8" diameter,
available in lengths of 23 3/4", 35 5/8", and 47 3/8"

High Luminous Flux

Produces 1200 lumens (23 3/4"), 1800 lumens (35 5/8"), and 2400 lumens (47 3/8") with an efficacy of 100 LM/W

Superior Color Rendering

90+ CRI for vibrant and accurate color representation

Flexible Color Temperatures

Available in 2700K, 3000K, 3500K, and 4000K

Advanced Dimming Control

Supports 0-10V, DALI-2, TUYA, and CASAMBI systems

Wide Beam Angle

200° x 110° for broad and effective illumination

Glare-Free Lighting

Low UGR for comfortable and effective illumination

TRACK MODULE ORDERING GUIDE

Basic Unit	Beam Angle	Driver	Voltage	Lumens	CCT	CRI	Finish
FRM-104-2 24" Linear Round Neon	WD 200° x 110° Distribution	DIM10 0-10V Dimming	48 48VDC	600L 600 lumens per foot	27K 2700K	90	BK Black Finish, Black Housing
FRM-104-3 36" Linear Round Neon		BLE-CASAMBI Bluetooth Low Energy Casambi			30K 3000K		
FRM-104-4 48" Linear Round Neon		DALI-2			35K 3500K		
		TUY TUYA			40K 4000K		

DESCRIPTION

Illuminate your space with the Round Neon Tube 206. These fixtures deliver up to 2400 lumens with a CRI of 90+ and a wide beam angle for expansive lighting. Available in various color temperatures and dimming options, they feature a sleek black finish and efficient design.

SPECIFICATIONS DATA

Lumens	600 LM/ft
Size(s)	1 1/8" x 24"/36"/48" L
Efficacy	100 LM/W
Finish(es)	Black
Driver(s)	0-10V, DALI-2, Tuya, CASAMBI
Input Voltage	48V
Beam Angle	200° x 110°
UGR	<10
CRI	>90
CCT	27K, 30K, 35K, 40K
Power (W)	6 W/ft

