



DESCRIPTION

The Dual-Hole Linear Module with Frosted Diffuser Distribution Lens is perfect for versatile indoor pendant lighting. Available in lengths of 47", 59", 71", and 95", it delivers up to 3600 lumens with a CRI of 90+ and a 110° beam angle. This fixture features various color temperatures and advanced dimming options, all in a sleek black finish.

FREEPOINT FEATURES

Slim Profile Design

7/8" W x 7/8" H, available in lengths of 47", 59", 71", and 95"

High Luminous Flux

Produces 1800 lumens (47"), 2250 lumens (59"), 2700 lumens (71"), and 3600 lumens (95") with an efficacy of 75 LM/W

Superior Color Rendering

90+ CRI for vibrant and accurate color representation

Flexible Color Temperatures

Available in 2700K, 3000K, 3500K, and 4000K

Advanced Dimming Control

Supports 0-10V, DALI-2, TUYA, and CASAMBI systems

Wide Beam Angle

110° for broad and even light distribution

Adjustable Mounting Height

Up to 59" for versatile installation options

SPECIFICATIONS DATA

Lumens	450 LM/ft
Size(s)	7/8" W x 48"/59"/71"/95" L
Efficacy	75 LM/W
Finish(es)	Black
Driver(s)	0-10V, DALI-2, Tuya, CASAMBI
Input Voltage	48V
Beam Angle	110°
Mounting Height	Adjustable up to 59"
CRI	>90
CCT	27K, 30K, 35K, 40K
Power (W)	6 W/ft

TRACK MODULE ORDERING GUIDE

Basic Unit	Beam Angle	Driver	Voltage	Lumens	CCT	CRI	Finish
FRM-106-4 48" Linear with Frosted Diffuser	110D 110° Distribution	DIM10 0-10V Dimming	48 48VDC	450L 450 lumens per foot	27K 2700K	90	BK Black Finish, Black Housing
FRM-106-5 59" Linear with Frosted Diffuser		BLE-CASAMBI Bluetooth Low Energy Casambi			30K 3000K		
FRM-106-6 71" Linear with Frosted Diffuser		DALI-2			35K 3500K		
FRM-106-8 95" Linear with Frosted Diffuser		TUY TUYA			40K 4000K		

