



DESCRIPTION

The Spotlight 201 is a powerful and efficient ceiling-mounted fixture. With 1020 lumens, CRI 90+, and beam angles of 24° and 36°, it's ideal for various indoor applications. Available in multiple color temperatures and dimming options, it combines performance and style in a sleek black finish.

FREEPOINT FEATURES

Compact Design

2" x 3 3/4" for discreet ceiling installations

High Luminous Flux

Delivers 1020 lumens with an efficacy of 85 LM/W

High Color Rendering Index

CRI of 90+ ensures accurate color representation

Versatile Color Temperatures

Available in 2700K, 3000K, 3500K, and 4000K

Advanced Dimming and Controls

Compatible with 0-10V, DALI-2, TUYA, and CASAMBI systems

Wide Beam Angle Options

Offered in 24° and 36° for focused or broader lighting

Low Glare

UGR <10 for comfortable and effective lighting

SPECIFICATIONS DATA

Lumens	1020
Size(s)	Ø 2" x 4-3/4" L
Efficacy	85 LM/W
Finish(es)	Black
Driver(s)	0-10V, DALI-2, Tuya, CASAMBI
Input Voltage	48V
Beam Angle	24°, 36°
UGR	<10
CRI	>90
CCT	27K, 30K, 35K, 40K
Power (W)	12

TRACK MODULE ORDERING GUIDE

Basic Unit	Beam Angle	Driver	Voltage	Lumens	CCT	CRI	Finish
FRM-301 1-5/8" Spotlight	24D 24° Distribution	DIM10 0-10V Dimming	48 48VDC	1020L 1020 lumens	27K 2700K	90	BK Black Finish, Black Housing
	36D 36° Distribution	BLE-CASAMBI Bluetooth Low Energy Casambi			30K 3000K		
					35K 3500K		
					40K 4000K		
	DALI-2						
	TUY TUYA						

