



FREEPOINT FEATURES

Slim Profile Design

7/8" W x 7/8" H, available in lengths of 24", 36", and 48"

High Luminous Flux

Produces 1200 lumens (24"), 1800 lumens (36"), and 2400 lumens (48") with an efficacy of 100 LM/W

Superior Color Rendering

90+ CRI for vibrant and accurate color representation

Flexible Color Temperatures

Available in 2700K, 3000K, 3500K, and 4000K

Advanced Dimming Control

Supports 0-10V, DALI-2, TUYA, and CASAMBI systems

Unique Beam Angle

90° x 45° x 15° for targeted illumination

Glare-Free Lighting

Low UGR for comfortable and effective illumination

TRACK MODULE ORDERING GUIDE

Basic Unit	Beam Angle	Driver	Voltage	Lumens	CCT	CRI	Finish
FRM-303-2 24" Linear with Wallwash Lens	WW Wallwash Distribution @ 90° x 45° x 15°	DIM10 0-10V Dimming	48 48VDC	600L 600 lumens per foot	27K 2700K	90	BK Black Finish, Black Housing
FRM-303-3 36" Linear with Wallwash Lens		BLE-CASAMBI Bluetooth Low Energy Casambi			30K 3000K		
FRM-303-4 48" Linear with Wallwash Lens		DALI-2			35K 3500K		
		TUY TUYA			40K 4000K		

DESCRIPTION

The Single-Hole Linear Module with Asymmetric Wall Wash Lens is perfect for versatile indoor lighting. Available in lengths of 24", 36", and 48", it delivers up to 2400 lumens with a CRI of 90+ and a unique beam angle. This fixture features various color temperatures and advanced dimming options, all in a sleek black finish.

SPECIFICATIONS DATA

Lumens	600 LM/ft
Size(s)	7/8" W x 24"/36"/48" L
Efficacy	100 LM/W
Finish(es)	Black
Driver(s)	0-10V, DALI-2, Tuya, CASAMBI
Input Voltage	48V
Beam Angle	90° x 45° x 15°
UGR	<10
CRI	>90
CCT	27K, 30K, 35K, 40K
Power (W)	6 W/ft

