



FREEPOINT FEATURES

Sleek Design

2" x 11 7/8" for a modern pendant installation

High Luminous Flux

Delivers 390 lumens with an efficacy of 65 LM/W

High Color Rendering Index

CRI of 90+ ensures accurate color representation

Versatile Color Temperatures

Available in 2700K, 3000K, 3500K, and 4000K

Advanced Dimming and Controls

Compatible with 0-10V, DALI-2, TUYA, and CASAMBI systems

Beam Angle Options

Offered in 24° and 36° for focused or broader lighting

Low Glare

UGR <10 for comfortable and effective lighting

TRACK MODULE ORDERING GUIDE

Basic Unit	Beam Angle	Driver	Voltage	Lumens	CCT	CRI	Finish
FRM-305 2" Cylinder Pendant with Direct/Indirect	24D 24° Distribution	DIM10 0-10V Dimming	48 48VDC	390L 390 lumens	27K 2700K	90	BK Black Finish, Black Housing
		BLE-CASAMBI Bluetooth Low Energy Casambi			30K 3000K		
	DALI-2				35K 3500K		
	36D 36° Distribution	TUY TUYA			40K 4000K		

DESCRIPTION

The Pendant Light 205 is an elegant and high-performance lighting fixture, ideal for indoor settings. It offers 390 lumens, a CRI of 90+, and beam angles of 24° and 36°. Available in various color temperatures and dimming options, it features a stylish black finish.

SPECIFICATIONS DATA

Lumens	390
Size(s)	Ø 2" x 11-3/4" L
Efficacy	65 LM/W
Finish(es)	Black
Driver(s)	0-10V, DALI-2, Tuya, CASAMBI
Input Voltage	48V
Beam Angle	24°, 36°
UGR	<10
CRI	>90
CCT	27K, 30K, 35K, 40K
Power (W)	6

