



### FREEPOINT FEATURES

#### Slim Profile Design

7/8" W x 7/8" H, available in lengths of 24", 36", and 48"

#### High Luminous Flux

Produces 1200 lumens (24"), 1800 lumens (35"), and 2400 lumens (48") with an efficacy of 100 LM/W

#### Superior Color Rendering

90+ CRI for vibrant and accurate color representation

#### Flexible Color Temperatures

Available in 2700K, 3000K, 3500K, and 4000K

#### Advanced Dimming Control

Supports 0-10V, DALI-2, TUYA, and CASAMBI systems

#### Unique Beam Angle

100° x 90° x 15° for targeted illumination

#### Glare-Free Lighting

Low UGR for comfortable and effective illumination

### TRACK MODULE ORDERING GUIDE

Basic Unit	Beam Angle	Driver	Voltage	Lumens	CCT	CRI	Finish
<b>FRM-403-2</b> 24" Linear with Batwing Lens	<b>BW</b> Batwing Distribution @ 100° x 90° x 15°	<b>DIM10</b> 0-10V Dimming	<b>48</b> 48VDC	<b>600L</b> 600 lumens per foot	<b>27K</b> 2700K	<b>90</b>	<b>BK</b> Black Finish, Black Housing
<b>FRM-403-3</b> 36" Linear with Batwing Lens		<b>BLE-CASAMBI</b> Bluetooth Low Energy Casambi			<b>30K</b> 3000K		
<b>FRM-403-4</b> 48" Linear with Batwing Lens		<b>DALI-2</b>			<b>35K</b> 3500K		
		<b>TUY</b> TUYA			<b>40K</b> 4000K		

### DESCRIPTION

The Single-Hole Linear Module with Batwing Distribution Lens is designed for versatile indoor lighting. Available in lengths of 24", 36", and 48", it delivers up to 2400 lumens with a CRI of 90+ and a unique beam angle. This fixture features various color temperatures and advanced dimming options, all in a sleek black finish.

### SPECIFICATIONS DATA

Lumens	600 LM/ft
Size(s)	7/8" W x 24"/36"/48" L
Efficacy	100 LM/W
Finish(es)	Black
Driver(s)	0-10V, DALI-2, Tuya, CASAMBI
Input Voltage	48V
Beam Angle	100° x 90° x 15°
UGR	<10
CRI	>90
CCT	27K, 30K, 35K, 40K
Power (W)	6 W/ft

