# Track Mounted PAR38 LED Wallwasher







W

### **Applications**

Maxima 38S W is an adjustable wallwasher designed for use with PAR38 retrofit LED lamps. MAX is a family of gracefully proportioned cylinders designed for low to very high ceilings.

## Features

- A concealed swivel provides 385° horizontal rotation and 0-90° tilt. The swivel is permanently tensioned, allowing the luminaire to remain fixed at the desired angle
- The optical assembly includes an integral specular reflector and a 40° x 70° spread lens, which work together to produce a floor-to-ceiling, side-to-side wash of light
- The assembly is fixed in place for precise aiming and can be easily removed as a unit for relamping

Complete Family	Wallwash (MAX-38-W)
SDCM	2-Step MacAdam Ellipse
Functionality	Wallwash
Finish	White, Black, Silver, RAL
Voltage	120V
Lifetime	L70 at 50000 Hours
Weight (lbs)	3
Listing	cSAus, c-UL-us





## Track Mounted PAR38 LED Wallwasher

#### EXAMPLE: MAX-38-W-120V-WH

Series Voltage Finish Options Optical Accessories

MAX-38-W 120V WH

BK SW OA-MAX-38-W-SL40X70 SI SB OA-MAX-38-W-LRS67 RAL OA-MAX-38-W-LRS50

Note: All extra optical accessories, aperture assemblies, and optics can be ordered separately. Check EPL Website for ordering nomenclature.

#### **Controls Options**

Can be specified with an on/off rocker switch on top of the fixture, for use on 120V track only.

#### Interchangeable Optical Accessories

- Combine optical accessories to effortlessly alter visual effects in the field
- The optical assembly accepts up to 2 optical accessories

#### Track Adaptor – Fully Concealed, Durable Locking

- Stainless steel clips lock fixture into our specially designed track systems. Two 'click' sounds indicate the fixture is secured into the track system
- Clips bite into aluminum, giving extremely durable ground connection
- Edison Price Lighting track systems are designed to completely conceal the adaptor for a clean profile
- Adaptors are shipped standard with all track fixtures. A Eutrac track adaptor can be used for mounting to Eutrac; 0-10V and DALI compatibility available. Contact factory for details

#### **Seamless Installation**

Fixtures may be configured to mount to any Edison Price Lighting recessed, suspended, surface-mounted track systems: <u>Sightline</u>, <u>Highline</u>, <u>Upline</u>, <u>Autobus</u>, <u>Eutrac</u>, and <u>Unicep</u>.

#### **Anodized Construction**

Heatsink is fabricated from extruded aluminum then undergoes a meticulous anodization process for a permanent and beautiful finish – increasing corrosion and heat resistance for long-lasting durability.

#### Carefully Applied, Low-VOC Finish

All Edison Price Lighting track fixtures are painted standard with low-VOC water-based paint – diminishing the release of toxic fumes – enhancing air quality and occupant health (unlike solvent-based paint).

#### **Optical Accessories**

- OA-MAX-38-W-5L40X70 (40° x 70° Spread Lens) -Delivers a rectangular beam recommended for illuminating wider artwork
- OA-MAX-38-W-LRS67 (67% Light Reduction Screen) -Reduces light by 67%, emitting 33% of total light; alternative to dimming
- OA-MAX-38-W-LRS50 (50% Light Reduction Screen) Reduces light by 50%, emitting 50% of total light; alternative to
- OA-MAX-38-W-DBL (Daylight Blue) Simulates daylight; ideal for museums, residential, & commercial
- OA-MAX-38-W-PK (Surprise Pink) Complements skin tones; perfect for hospitality applications
- OA-MAX-38-W-AMB Amber Color Filter
- OA-MAX-38-W-BL Blue Color Filter
- OA-MAX-38-W-GR Green Color Filter
- OA-MAX-38-W-RD Red Color Filter
- OA-MAX-38-W-RAL (Rosco Custom Color) Consult factory for a brilliant Rosco filter in any color. Click <u>here</u> to see more information on color filters selection

#### river)

Fixture is cULus-listed for mounting on Edison Price Lighting 120V track only.

### **Dimming & Driver Information**

Consult the lamp manufacturer for dimming compatibility.

#### Warranty

Five-year warranty not including providing extraordinary means of access, such as scaffolding or lifts, to service our products.

#### Listings

- cSAus
- c-UL-us

