

# 5" Artima/5

## Track Mounted LED 5° Spotlight

A5-VNSP



OH



OG

### Applications

Artima/5 is a minimalistic, high-lumen track-mounted luminaire suitable for 15'-25' ceilings. The modern & lasting design of Artima is desired by contemporary, world-renowned museums.

### Features

- Signature Low Aperture Brightness: Expertly engineered optical system produces extremely low aperture brightness, desired by museums, galleries, and other architectural applications
- Lockable Aiming: Achieve 385° rotation, 0-90° tilt, and fully lock adjustment using a hex key
- A very focused 5° beam, delivering a sharp yet subtle spot and achieving up to 114,900 CBCP
- The optical assembly accepts up to 2 extra accessories for additional refining of the beam and visual effect in the field
- Selected for the IES Progress Report

### Ring Baffle (A5-VNSP-OG)

- A specially designed Ring Baffle (OG) refines the beam by eliminating stray light and enhancing glare control for a very focused, crisp spotlight
- Ring Baffle trims all light beyond 5°, achieving up to 114,900 CBCP

### Open Aperture (A5-VNSP-OH)

Open Aperture (OH) for maximum efficacy; for use with interchangeable reflectors in a variety of beam spreads.

### Notable Projects

Arlington Street Church  
Lucas Museum of Narrative Art  
Meadows Museum

<b>Series</b>	A5-VNSP-OH (Open Aperture), A5-VNSP-OG (Ring Baffle)
<b>Complete Family</b>	Standard (A5), Narrow Spot (A5-NSP), Very Narrow Spot (A5-VNSP), Wallwash (A5-W)
<b>Lumens</b>	1200, 1500, 2000, 2500
<b>CCT</b>	27K, 30K, 35K, 40K, 50K
<b>CRI</b>	90+ Standard, XIA-95+
<b>SDCM</b>	2-Step MacAdam Ellipse
<b>Optics / Beam Angles</b>	5°
<b>Finish</b>	White, Black, Silver
<b>Dimming</b>	DIMTR, LTEA2W, BLE, DIMTR-IDM
<b>Voltage</b>	120V, 277V (Non-Dimmable)
<b>Control Capabilities</b>	IDM, Bluetooth
<b>Lifetime</b>	L70 at 50000 Hours
<b>Weight (lbs)</b>	6
<b>Listing</b>	cSAus, c-UL-us



# 5" Artima/5

A5-VNSP

## Track Mounted LED 5° Spotlight

EXAMPLE: **A5-VNSP-OH-1200L-27K-90-5D-DIMTR-120V-WH**

Series	Aperture Assembly	Lumens	CCT	CRI	Optics	Driver	Voltage	Finish	Optical Accessories	Barn Doors
<b>A5-VNSP</b>	<b>OH</b>	<b>1200L</b>	<b>27K</b>	<b>90+</b>	<b>5D</b>	<b>DIMTR</b>	<b>120V</b>	<b>WH</b>	-	-
	(Open Aperture)	<b>1500L</b>	<b>30K</b>	<b>XIA-95+</b>		<b>LTEA2W</b>	<b>277V</b>	<b>BK</b>	<b>OA-A5-VNSP-SOL</b>	<b>BD-WH</b>
	<b>OG</b>	<b>2000L</b>	<b>35K</b>			<b>NON-DIM</b>	<b>(Non-Dim Only)</b>	<b>SI</b>	<b>OA-A5-VNSP-SL20X55</b>	<b>BD-BK</b>
	(Ring Baffle)	<b>2500L</b>	<b>40K</b>			<b>BLE</b>			<b>OA-A5-VNSP-SL40X70</b>	<b>BD-SI</b>
			<b>50K</b>			<b>DIMTR-IDM</b>			<b>OA-A5-VNSP-SL30</b>	<b>BD-RAL</b>
			<b>(50K Is Not Compatible with XIA-95+)</b>		<b>(Integral Rotary Dimming Module)</b>			<b>OA-A5-VNSP-SL70</b>		
									<b>OA-A5-VNSP-BM</b>	
									<b>OA-A5-VNSP-LRS67</b>	
									<b>OA-A5-VNSP-LRS50</b>	

**Note:** All extra optical accessories, aperture assemblies, and optics can be ordered separately. Check [EPL Website](#) for ordering nomenclature.

### Optical Purity

- Ridged pattern on the inner surface of the external reflector transmits the beam spread
- A beam smoother softens the light and comes standard; may be replaced with up to 2 optical accessories

### Twist-and-Lock Optical Reflector

Field-interchangeable internal 'twist-and-lock' reflector is available in a variety of beam spreads – enabling the same luminaire to accommodate different optical distributions.

### Interchangeable Optical Accessories

Combine optical accessories to effortlessly alter visual effects in the field.

- Both OG and OH aperture assemblies accept up to 2 optical accessories
- A complimentary beam smoother is included with either assembly

### Track Adaptor – Fully Concealed, Durable Locking

- Stainless steel clips lock fixture into our specially designed track systems. Two 'click' sounds indicate the fixture is secured into the track system
- Clips bite into aluminum, giving extremely durable ground connection
- Edison Price Lighting track systems are designed to completely conceal the adaptor for a clean profile
- Adaptors are shipped standard with all track fixtures. A Eutrac track adaptor can be used for mounting to Eutrac; 0-10V and DALI compatibility available. Contact factory for details

### Seamless Installation

Fixtures may be configured to mount to any Edison Price Lighting recessed, suspended, surface-mounted track systems: [Sightline](#), [Highline](#), [Upline](#), [Autobus](#), [Eutrac](#), and [Unicep](#).

### Anodized Construction

Heatsink is fabricated from extruded aluminum then undergoes a meticulous anodization process for a permanent and beautiful finish – increasing corrosion and heat resistance for long-lasting durability.

### Carefully Applied, Low-VOC Finish

All Edison Price Lighting track fixtures are painted standard with low-VOC water-based paint – diminishing the release of toxic fumes – enhancing air quality and occupant health (unlike solvent-based paint).

### Optical Accessories

- OA-A5-VNSP-SOL** (Solite Lens) - Stipple-patterned lens to appreciably diffuse the light
- OA-A5-VNSP-SL20X55** (20° x 55° Spread Lens) - Delivers a rectangular beam recommended for illuminating medium-sized artwork
- OA-A5-VNSP-SL40X70** (40° x 70° Spread Lens) - Delivers a rectangular beam recommended for illuminating wider artwork
- OA-A5-VNSP-SL30** (30° Spread Lens) - One-way 30° lateral lens recommended for use with an object light; based on internal beam spread, can elongate the light source vertically or side-to-side
- OA-A5-VNSP-SL70** (70° Spread Lens) - One-way 70° lateral lens recommended for use with an object light; based on internal beam spread, can elongate the light source vertically or side-to-side
- OA-A5-VNSP-BM** (Beam Smoother) - Removes striations from the light source for a subtle wash of light
- OA-A5-VNSP-LRS67** (67% Light Reduction Screen) - Reduces light by 67%, emitting 33% of total light; alternative to dimming
- OA-A5-VNSP-LRS50** (50% Light Reduction Screen) - Reduces light by 50%, emitting 50% of total light; alternative to dimming
- OA-A5-VNSP-DBL** (Daylight Blue) - Simulates daylight; ideal for museums, residential, & commercial
- OA-A5-VNSP-PK** (Surprise Pink) - Complements skin tones; perfect for hospitality applications
- OA-A5-VNSP-AMB** - Amber Color Filter
- OA-A5-VNSP-BL** - Blue Color Filter
- OA-A5-VNSP-GR** - Green Color Filter
- OA-A5-VNSP-RD** - Red Color Filter
- OA-A5-VNSP-RAL** (Rosco Custom Color) - Consult factory for a brilliant Rosco filter in any color. Click [here](#) to see more information on color filters selection
- BD** (Barn Doors) - Shapes a tight beam of light for a theatrical effect ideal for children's, science, and historical museums

### XIA-95+ (Xicato)

- XTM Artist Series, XIM Integral Bluetooth Module (BLE + LED), or XOB (COB array light source in as small as 4.5mm form and up to 8300 lumens)
- Best color-matching: within 1 x 2 MacAdam Ellipse
- Up to 95+ CIE CRI
- Module varies by product family and fixture function.

### BLE Xicato XID Intelligent Drivers

Powered by Xicato XID (Intelligent Drivers), constant-current drivers that enable Bluetooth controls.

- Dimmable down to 0.1%
- Meets IEEE 1789 recommendations for flicker
- Group or individual remote control via a slide switch
- Bluetooth and IDM can be specified in the same fixture, to allow switching between the two options

### IDM (Integral Dimming Module) Option

- 120V track only; dim down to 10% using an integral rotary dimmer on the driver case
- Spring-loaded dimmer control shaft can be depressed flush with the driver case to enforce dimmer setting. 'Clock face' markings register dimmer setting

### Driver

120/277V 50/60Hz; Flicker-free 1% dimming standard; THD < 20%; power factor >.09. Thermally protected. On/off rocker switch is mounted on the exterior of the driver box; included standard for 120V

### Dimming & Driver Information

**DIMTR** - Triac, incandescent, and electronic low voltage (ELV) dimming down to 5% in 120V only  
**LTEA2W** - Hi-lume 1% 2-Wire 120V Forward-Phase Control  
**NON-DIM** - 120 or 277V Non-Dimming Control  
**BLE** - Xicato XIM Bluetooth Integral Module/Xicato XID Intelligent Driver (Consult Factory For Info)  
**DIMTR-IDM** - Integral Rotary Dimming Module

### Warranty

Five-year warranty not including providing extraordinary means of access, such as scaffolding or lifts, to service our products.

### Listings

- cSAus
- c-UL-us



# 5" Artima/5

Track Mounted LED 5° Spotlight

A5-VNSP

