

5" Artima/5

Track Mounted LED Luminaire

A5



OH



OX

Applications

Artima/5 is a minimalistic, high-lumen track-mounted luminaire suitable for 15'-25' ceilings. The modern & lasting design of Artima is desired by contemporary, world-renowned museums.

Features

- Signature Low Aperture Brightness: Expertly engineered optical system produces extremely low aperture brightness, desired by museums, galleries, and other architectural applications
- Lockable Aiming: Achieve 385° rotation, 0-90° tilt, and fully lock adjustment using a hex key
- The optical assembly accepts up to 2 extra accessories for additional refining of the beam and visual effect

Cross Baffle (A5-OX)

- The Cross Baffle (OX) is preferred by museums, which require low-glare illumination and quiet ceilings
- Eliminates glare; controls stray light; and conceals the source from normal viewing angles
- While using the Cross Baffle, the luminaire can accept up to 2 extra optical accessories for additional refining of the beam and visual effect

Open Aperture (A5-OH)

Open Aperture (OH) for maximum efficacy; for use with interchangeable reflectors in a variety of beam spreads.

Notable Projects

Park Avenue Armory
Christ Cathedral
Saint Thomas Church
Brooklyn Museum

| | |
|-----------------------------|--|
| Series | A5-OH (Open Aperture), A5-OX (Cross Baffle) |
| Complete Family | Standard (A5), Narrow Spot (A5-NSP), Very Narrow Spot (A5-VNSP), Wallwash (A5-W) |
| Lumens | 2000, 2500, 3000, 3500, 4000, 4500, 5000, 5500, 7000 |
| CCT | 27K, 30K, 35K, 40K, 50K |
| CRI | 90+ Standard, XIA-95+ |
| SDCM | 2-Step MacAdam Ellipse |
| Optics / Beam Angles | 15°, 16°, 21°, 28°, 38°, 40° |
| Finish | White, Black, Silver |
| Dimming | DIMTR, LTEA2W, BLE, DIMTR-IDM |
| Voltage | 120V, 277V (Non-Dimmable) |
| Control Capabilities | IDM, Bluetooth |
| Lifetime | L70 at 50000 Hours |
| Weight (lbs) | 6 |
| Listing | cSAus, c-UL-us |



5" Artima/5

Track Mounted LED Luminaire

EXAMPLE: **A5-OH-2000L-27K-90-15D-DIMTR-120V-WH**

| Series | Aperture Assembly | Lumens | CCT | CRI | Optics | Driver | Voltage | Finish | Optical Accessories | Barn Doors |
|-----------|-------------------|--------------|---|----------------|------------|---|-----------------------|-----------|----------------------|---------------|
| A5 | OH | 2000L | 27K | 90+ | 15D | DIMTR | 120V | WH | - | - |
| | (Open Aperture) | 2500L | 30K | XIA-95+ | 16D | LTEA2W | 277V | BK | OA-A5-SOL | BD-WH |
| | OX | 3000L | 35K | | 21D | NON-DIM | (Non-Dim Only) | SI | OA-A5-SL20X55 | BD-BK |
| | (Cross Baffle) | 3500L | 40K | | 28D | BLE | | | OA-A5-SL40X70 | BD-SI |
| | | 4000L | 50K | | 38D | DIMTR-IDM | | | OA-A5-SL30 | BD-RAL |
| | | 4500L | (50K Is Not Compatible with XIA-95+) | | 40D | (Integral Rotary Dimming Module) | | | OA-A5-SL70 | |
| | | 5000L | | | | | | | OA-A5-LRS67 | |
| | | 5500L | | | | | | | OA-A5-LRS50 | |
| | | 7000L | | | | | | | | |

Note: All extra optical accessories, aperture assemblies, and optics can be ordered separately. Check [EPL Website](#) for ordering nomenclature.

Optical Purity

- Ridged pattern on the inner surface of the external reflector transmits the beam spread
- A beam smoother softens the light and comes standard; may be replaced with up to 2 optical accessories

Twist-and-Lock Optical Reflector

Field-interchangeable internal 'twist-and-lock' reflector is available in a variety of beam spreads – enabling the same luminaire to accommodate different optical distributions.

Interchangeable Optical Accessories

Combine optical accessories to effortlessly alter visual effects in the field.

- Both OX and OH aperture assemblies accept up to 2 optical accessories.
- With the OX assembly, lens orientation may be adjusted by rotating the Cross Baffle
- A complimentary beam smoother is included with either assembly

Track Adaptor – Fully Concealed, Durable Locking

- Stainless steel clips lock fixture into our specially designed track systems. Two 'click' sounds indicate the fixture is secured into the track system
- Clips bite into aluminum, giving extremely durable ground connection
- Edison Price Lighting track systems are designed to completely conceal the adaptor for a clean profile
- Adaptors are shipped standard with all track fixtures. A Eutrac track adaptor can be used for mounting to Eutrac; 0-10V and DALI compatibility available. Contact factory for details

Seamless Installation

Fixtures may be configured to mount to any Edison Price Lighting recessed, suspended, surface-mounted track systems: [Sightline](#), [Highline](#), [Upline](#), [Autobus](#), [Eutrac](#), and [Unicep](#).

Anodized Construction

Heatsink is fabricated from extruded aluminum then undergoes a meticulous anodization process for a permanent and beautiful finish – increasing corrosion and heat resistance for long-lasting durability.

Carefully Applied, Low-VOC Finish

All Edison Price Lighting track fixtures are painted standard with low-VOC water-based paint – diminishing the release of toxic fumes – enhancing air quality and occupant health (unlike solvent-based paint).

Optical Accessories

- OA-A5-SOL** (Solite Lens) - Stipple-patterned lens to appreciably diffuse the light
- OA-A5-SL20X55** (20° x 55° Spread Lens) - Delivers a rectangular beam recommended for illuminating medium-sized artwork
- OA-A5-SL40X70** (40° x 70° Spread Lens) - Delivers a rectangular beam recommended for illuminating wider artwork
- OA-A5-SL30** (30° Spread Lens) - One-way 30° lateral lens recommended for use with an object light; based on internal beam spread, can elongate the light source vertically or side-to-side
- OA-A5-SL70** (70° Spread Lens) - One-way 70° lateral lens recommended for use with an object light; based on internal beam spread, can elongate the light source vertically or side-to-side
- OA-A5-LRS67** (67% Light Reduction Screen) - Reduces light by 67%, emitting 33% of total light; alternative to dimming
- OA-A5-LRS50** (50% Light Reduction Screen) - Reduces light by 50%, emitting 50% of total light; alternative to dimming
- OA-A5-DBL** (Daylight Blue) - Simulates daylight; ideal for museums, residential, & commercial
- OA-A5-PK** (Surprise Pink) - Complements skin tones; perfect for hospitality applications
- OA-A5-AMB** - Amber Color Filter
- OA-A5-BL** - Blue Color Filter
- OA-A5-GR** - Green Color Filter
- OA-A5-RD** - Red Color Filter
- OA-A5-RAL** (Rosco Custom Color) - Consult factory for a brilliant Rosco filter in any color. Click [here](#) to see more information on color filters selection
- BD** (Barn Doors) - Shapes a tight beam of light for a theatrical effect ideal for children's, science, and historical museums

XIA-95+ (Xicato)

- XTM Artist Series, XIM Integral Bluetooth Module (BLE + LED), or XOB (COB array light source in as small as 4.5mm form and up to 8300 lumens)
- Best color-matching: within 1 x 2 MacAdam Ellipse
- Up to 95+ CIE CRI
- Module varies by product family and fixture function.

BLE Xicato XID Intelligent Drivers

Powered by Xicato XID (Intelligent Drivers), constant-current drivers that enable Bluetooth controls.

- Dimmable down to 0.1%
- Meets IEEE 1789 recommendations for flicker
- Group or individual remote control via a slide switch
- Bluetooth and IDM can be specified in the same fixture, to allow switching between the two options

IDM (Integral Dimming Module) Option

- 120V track only; dim down to 10% using an integral rotary dimmer on the driver case
- Spring-loaded dimmer control shaft can be depressed flush with the driver case to enforce dimmer setting. 'Clock face' markings register dimmer setting

Driver

120/277V 50/60Hz; Flicker-free 1% dimming standard; THD < 20%; power factor >.09. Thermally protected. On/off rocker switch is mounted on the exterior of the driver box; included standard for 120V

Dimming & Driver Information

DIMTR - Triac, incandescent, and electronic low voltage (ELV) dimming down to 5% in 120V only
LTEA2W - Hi-lume 1% 2-Wire 120V Forward-Phase Control
NON-DIM - 120 or 277V Non-Dimming Control
BLE - Xicato XIM Bluetooth Integral Module/Xicato XID Intelligent Driver (Consult Factory For Info)
DIMTR-IDM - Integral Rotary Dimming Module

Warranty

Five-year warranty not including providing extraordinary means of access, such as scaffolding or lifts, to service our products.

Listings

- cSAus
- c-UL-us



5" Artima/5

Track Mounted LED Luminaire

A5

