


10"

Architectural LED Downlight - Retrofit

EPD-J10

Edison Series



Application

A complete family of downlights, accent lights, wallwashers, double wallwashers, and corner wallwashers in multiple beam spreads and apertures designed for commercial, civic, museums, corporate, hospitality, academic, retail, medical, and houses of worship.

Features

- Exceptional Optical Quality: Up to 98 CRI, 1×2 Step MacAdam Ellipse.
- Shipped standard with a Solite Beam Smoother lens that removes striations from the light source.
- Available with a multitude of dimming protocols and control offerings.

Lumens	900, 1200, 1500, 2000, 3000, 4000, 6000, 8000 ⁶
CCT & Dynamic Platforms	22K, 27K, 30K, 35K, 40K, 50K Dims to Warm: 30K-18K, 30K-22K or 27K-18K Xicato Artist: 27K, 30K, 35K, 40K, 30K-VIB Natural Spectrum: 27K, 30K, 35K, 40K, 50K, 65K
CRI	90+ Standard, 98+ ²
Color Quality	2 Step MacAdam Ellipse
Distributions	NSPD (15°), SPD (24°), ND (30°), MD (36°), MWD (52°), WD (60°), VWD (70°)
Trim Options	Downlight, Wall Wash, Double Wall Wash, Corner Wall Wash, Wet Location
Reflector Colors	CL (Semi-Specular Chrome), SHZ (Low Iridescent Satin Haze), WT (Wheat), W (White), BK (Black), BZ (Bronze)
Flange Colors	TL (Trimless), WH (Self-Flanged White), SCH (Self-Flanged Semi-Specular Chrome), SHZ (Self-Flanged Low Iridescent Satin Haze), BK (Self-Flanged Black), BZ (Self-Flanged Bronze)
Dimming	DIM10, LUTH, LUT2W ³ , LUTFTB ⁴ , ELDO10.1, ELDODMX.1, ELDODALI.1, DIMTR ³ , BLE-CASAMBI
Emergency	EMG-LED-10W, EMG-LED-20W, INTG-EMG-LED-10W, INTG-EMG-LED-20W, EMG-SDT-LED-10W
Lifetime	L70 at 102,000 Hours
Photometric Tests	In Accordance with IES LM79-08, LM80 and TM-30, TM-21



10"

EPD-J10

Edison Series

Architectural LED Downlight - Retrofit

PART NUMBER: **EPD-J10-900L-22K-90-NSPD-DIM10-120V**

Series	Lumens	CCT	CRI	Optics	Drivers	Voltage	Emergency	Options
EPD-J10	900L	22K	90+	NSPD	DIM10	120V	-	-
	1200L	27K	98+ 2	SPD	LUTH	277V	EMG-LED-10W	USA
	1500L	30K		ND	LUT2W 3	MVOLT	EMG-LED-20W	
	2000L	35K		MD	LUTFTB 4	347V 5	INTG-EMG-LED-10W	
	3000L	40K		MWD	ELDO10.1		INTG-EMG-LED-20W	
	4000L	50K 1		WD	ELDODMX.1		EMG-SDT-LED-10W	
	6000L			VWD	ELDODALI.1			
8000L 6				DIMTR 3				
				BLE-CASAMBI				

1 50K series are available with 85+ CRI only 2 98+ CRI is available in 27K, 30K and 40K only 3 DIMTR and LUT2W available for luminaires up to 4000L in 120V only
 4 LUTFTB Available for luminaires up to 1500L 5 347V is available in only DIM10 6 The 8000L is available in only DIM10

PART NUMBER: **EPD-J10-WDM-30K-18K-900L-90-NSPD-DIM10-120V**

Series	Technology	Lumens	CRI	Optics	Drivers	Voltage	Emergency	Options
EPD-J10 <i>(Dim to Warm)</i>	WDM-30K-18K	900L	90+	NSPD	DIM10	120V	-	-
	WDM-30K-22K	1200L		SPD	LUTH	277V	EMG-LED-10W	USA
	WDM-27K-18K	1500L		ND	LUT2W 1	MVOLT	EMG-LED-20W	
		2000L		MD	LUTFTB 2		INTG-EMG-LED-10W	
		3000L		MWD	DIMTR 1		INTG-EMG-LED-20W	
		4000L		WD	ELDO10.1		EMG-SDT-LED-10W	
				VWD	ELDODALI.1			
				ELDODMX.1				
				BLE-CASAMBI				

1 DIMTR and LUT2W available in 120V only 2 LUTFTB Available for luminaires up to 1500L 3 CP Available for luminaires up to 1500L

PART NUMBER: **EPD-J10-XIA-900L-27K-98-NSPD-DIM10-120V**

Series	Technology	Lumens	CCT	CRI	Optics	Drivers	Voltage	Emergency	Options
EPD-J10 <i>(Xicato Artist)</i>	XIA	900L	27K	98+	NSPD	DIM10	120V	-	-
		1200L	30K		SPD	LUTH	277V	EMG-LED-10W	USA
		1500L	30K-VIB		ND	LUT2W 1	MVOLT	EMG-LED-20W	
		2000L	35K		MD	LUTFTB 2	347V 3	INTG-EMG-LED-10W	
		3000L	40K		MWD	ELDO10.1		INTG-EMG-LED-20W	
					WD	ELDODMX.1		EMG-SDT-LED-10W	
			VWD	ELDODALI.1					
				DIMTR 1					
				BLE-CASAMBI					

1 DIMTR and LUT2W available in 120V only 2 LUTFTB Available for luminaires up to 1500L 3 347V is available in only DIM10

10"

Architectural LED Downlight - Retrofit

EPD-J10



Edison Series

PART NUMBER: **EPD-J10-NSL-900L-27K-97-NSPD-DIM10-120V**

Series	Technology	Lumens	CCT	CRI	Optics	Drivers	Voltage	Emergency	Options
EPD-J10 <i>(Natural Spectrum)</i>	NSL	900L	27K	97+	NSPD	DIM10	120V	-	-
		1200L	30K		SPD	LUTH	277V	EMG-LED-10W	USA
		1500L	35K		ND	LUT2W ¹	MVOLT	EMG-LED-20W	
		2000L	40K		MD	LUTFTB ²	347V ³	INTG-EMG-LED-10W	
		3000L	50K		MWD	ELDO10.1		INTG-EMG-LED-20W	
		65K	WD	ELDODMX.1		EMG-SDT-LED-10W			
			VWD	ELDODALI.1					
					DIMTR ¹				
					BLE-CASAMBI				

¹ DIMTR and LUT2W available in 120V only ² LUTFTB Available for luminaires up to 1500L ³ 347V is available in only DIM10

ORDER GUIDE

REFLECTOR TYPE				MOUNTING	COLOR					
REFLECTOR TYPE				MOUNTING	COLOR					
Open Downlight EPD-10-101	Wall Wash EPD-10-107	Double Wall Wash EPD-10-177	Corner Wall Wash ?	Flanged 	ANODIZED FLANGED					
					Clear White CL-WH	Satin Haze White SHZ-WH	Black BK-BK			
					Clear Semi-Spec CL-SCH	White WH-WH	Satin Haze SHZ-SHZ			
								Clear Black CL-BK	Black White BK-WH	Wheat White WT-WH
Open Downlight EPD-10-TL-101	Wall Wash EPD-10-TL-107			Trimless 	ANODIZED TRIMLESS					
					White WH	Black BK	Clear CL	Satin Haze SHZ		



WWW.EPL.COM | 718.685.0700 | NEW YORK / LOS ANGELES

