



## LINEAR

### FREE SERIES MODULE FEATURES

**Compact Dimensions:**

Length 12" / 24" / 36" x Width 7/8" x Height 1 5/8", ideal for discreet installation

**High Efficiency:**

Consumes 7W / 14W / 20W of power while providing 980LM / 1960LM / 2800LM of light output

**Wide Beam Angle:**

100° beam angle for broad and even illumination

**Advanced Dimming and Controls:**

Compatible with Non-dimming, DALI, CASAMBI, and 0-10V systems for versatile control

**Durable Finish:**

Black coating with an IP20 rating, suitable for indoor environments

**Easy Installation:**

Designed for track mounting, ensuring a hassle-free setup

### TRACK MODULE ORDERING GUIDE

Basic Unit	Beam Angle	Driver	Voltage	Lumens	CCT	CRI	Finish
<b>FR-103-1</b> 12" Linear w/ Frosted Diffuser	<b>FD</b> 100° Distribution	<b>DIM10</b> 0-10V Dimming	<b>48</b> 48VDC	<b>2800L</b> 2800 lumens	<b>27K</b> 2700K	<b>90</b>	<b>BK</b> Black Finish, Black Housing
<b>FR-103-2</b> 24" Linear w/ Frosted Diffuser		<b>BLE-CASAMBI</b> Bluetooth Low Energy Casambi		<b>1960L</b> 1960 lumens	<b>30K</b> 3000K		
<b>FR-103-3</b> 36" Linear w/ Frosted Diffuser		<b>DALI-2</b>		<b>980</b> 980 lumens	<b>35K</b> 3500K		
		<b>TUY</b> TUYA			<b>40K</b> 4000K		

### DESCRIPTION

The Free Series Track-Mounted LED Linear Module combines sleek design with high performance, perfect for versatile indoor lighting applications. With high CRI and multiple CCT options, it ensures vibrant and accurate color rendering with a wide beam angle for even illumination.

### SPECIFICATIONS DATA

<b>Lens</b>	Frosted Diffuser
Lumens	2800 / 1960 / 980
Size(s)	7/8" x 1-5/8" x 12, 24, 36"
Finish(es)	Black
Driver(s)	0-10V, DALI-2, Tuya, CASAMBI
Input Voltage	48V
Beam Angle	100°
CRI	>90
CCT	27K, 30K, 35K, 40K
Power (W)	20 / 14 / 7





