



NEON

FREEPOINT FEATURES

Compact Dimensions:

Diameter 1 3/16" x Length 23 5/8" / 35 7/16" / 47 1/4", ideal for versatile installation

High Efficiency:

Consumes 12W / 18W / 24W of power while providing 1200LM / 1800LM / 2400LM of light output

PC Diffuser:

Provides even and soft light distribution with a 100° beam angle

Advanced Dimming and Controls:

Compatible with Non-dimming, DALI, CASAMBI, and 0-10V systems for versatile control

Durable Finish:

Black coating with an IP20 rating, suitable for indoor environments

Easy Installation

DESCRIPTION

The Free Series Track-Mounted Neon LED Module blends stylish design with high performance, making it perfect for decorative indoor lighting applications. Featuring a PC diffuser and high CRI, it provides vibrant and uniform illumination across multiple CCT options.

SPECIFICATIONS DATA

Lumens	2400 / 1800 / 1200
Size(s)	Ø 1-3/16" x 24, 36, 48"
Finish(es)	Black
Driver(s)	0-10V, DALI-2, Tuya, CASAMBI
Input Voltage	48V
Beam Angle	100°
CRI	>90
CCT	27K, 30K, 35K, 40K
Power (W)	24 / 18 / 12

TRACK MODULE ORDERING GUIDE

PIVOT



Basic Unit	Beam Angle	Driver	Voltage	Lumens	CCT	CRI	Finish
FR-104-2 24" Rigid Neon Linear	100D 100° Distribution	DIM10 0-10V Dimming	48 48VDC	2400L 2400 lumens	27K 2700K	90	BK Black Finish, Black Housing
FR-104-3 36" Rigid Neon Linear		BLE-CASAMBI Bluetooth Low Energy Casambi		1800L 1800 lumens	30K 3000K		
FR-104-4 48" Rigid Neon Linear		DALI-2		1200L 1200 lumens	35K 3500K		
		TUY TUYA			40K 4000K		

