



FREE SERIES MODULE FEATURES

Compact Dimensions:

Diameter 1 9/16" x Height 3 15/16", ideal for elegant installations

High Efficiency:

Consumes only 3W of power while providing 470LM of light output

Lens Diffuser:

Provides soft and even light distribution at 110° beam angle

Advanced Dimming and Controls:

Compatible with Non-dimming, DALI, CASAMBI, and 0-10V systems for versatile control

Durable Finish:

Black coating with an IP20 rating, suitable for indoor environments

Easy Installation:

Designed for track mounting, ensuring a hassle-free setup

DESCRIPTION

The Free Series Track-Mounted Decorative Waterdrop Pendant Light combines a unique design with high performance, making it ideal for decorative indoor lighting applications. Featuring a lens diffuser and high CRI, it delivers soft and vibrant illumination with multiple CCT options.

SPECIFICATIONS DATA

| | |
|---------------|------------------------------|
| Lumens | 470 |
| Size(s) | Ø 1-9/16" x 3-15/16" |
| Finish(es) | Black |
| Driver(s) | 0-10V, DALI-2, Tuya, CASAMBI |
| Input Voltage | 48V |
| Beam Angle | 110° |
| CRI | >90 |
| CCT | 27K, 30K, 35K, 40K |
| Power (W) | 3 |

TRACK MODULE ORDERING GUIDE

| Basic Unit | Beam Angle | Driver | Voltage | Lumens | CCT | CRI | Finish |
|---------------------------------------------------|---------------------------|------------------------------------------------|-------------|--------------------|--------------|-----|--------------------------------------|
| FR-505 Ø 1-9/16" Waterdrop Pendant Light | 110D 110° Distribution | DIM10 0-10V Dimming | 48 48VDC | 470L 470 lumens | 27K 2700K | 90 | BK Black Finish, Black Housing |
| | | BLE-CASAMBI Bluetooth Low Energy Casambi | | | 30K 3000K | | |
| | | DALI-2 | | | 35K 3500K | | |
| | | TUY TUYA | | | 40K 4000K | | |

