



## ADJ. LINEAR

### FREEPOINT FEATURES

**Compact Dimensions:**

Length 4 5/16" / 8 11/16" x Width 7/8" x Height 4 1/8", ideal for discreet installation

**High Efficiency:**

Consumes 6W / 12W of power while providing 420LM / 840LM of light output

**Grating Diffuser:**

Ensures precise and uniform light distribution with beam angles of 30° and 40°

**Adjustable Tilt:**

Features a 90° tilt for flexible lighting adjustments

**Advanced Dimming and Controls:**

Compatible with Non-dimming, DALI, CASAMBI, and 0-10V systems for versatile control

**Easy Installation:**

Designed for track mounting, ensuring a hassle-free setup

### DESCRIPTION

The Free Series Track-Mounted LED Adjustable Linear Module offers sophisticated design and high performance, ideal for various indoor lighting applications. Featuring a grating diffuser, high CRI, and multiple CCT options, it ensures precise and uniform light distribution.

### SPECIFICATIONS DATA

<b>Lens</b>	Microcell (Grating)
Lumens	840 / 420
Size(s)	7/8" x 1-5/8" x Lengths
Finish(es)	Black
Driver(s)	0-10V, DALI-2, Tuya, CASAMBI
Input Voltage	48V
Beam Angle	30° / 55°
CRI	>90
CCT	27K, 30K, 35K, 40K
Power (W)	12 / 6



### TRACK MODULE ORDERING GUIDE

Basic Unit	Beam Angle	Driver	Voltage	Lumens	CCT	CRI	Finish
<b>FR-603-1</b> 4-7/16" Adj. Linear w/ Microcell Lens	<b>GR30</b> 30° Distribution	<b>DIM10</b> 0-10V Dimming	<b>48</b> 48VDC	<b>840L</b> 840 lumens	<b>27K</b> 2700K	<b>90</b>	<b>BK</b> Black Finish, Black Housing
<b>FR-603-2</b> 8-11/16" Adj. Linear w/ Microcell Lens		<b>BLE-CASAMBI</b> Bluetooth Low Energy Casambi					
<b>FR-603-3</b> 17-3/16" Adj. Linear w/ Microcell Lens		<b>DALI-2</b>					
		<b>TUY</b> TUYA			<b>35K</b> 3500K		
				<b>420L</b> 420 lumens	<b>40K</b> 4000K		



