



FREEPOINT FEATURES

Slim Profile Design

7/8" W x 7/8" H, available in lengths of 51" and 77"

High Luminous Flux

Produces 1820 lumens (51") and 2730 lumens (77") with an efficacy of 70 LM/W

Superior Color Rendering

90+ CRI for vibrant and accurate color representation

Flexible Color Temperatures

Available in 2700K, 3000K, 3500K, and 4000K

Advanced Dimming Control

Supports 0-10V, DALI-2, TUYA, and CASAMBI systems

Focused Beam Angles

30° and 55° for the 51" model and 77"

Adjustable Mounting Height

Up to 59" for versatile installation options

TRACK MODULE ORDERING GUIDE

Basic Unit	Beam Angle	Driver	Voltage	Lumens	CCT	CRI	Finish
FRM-606-4 51" Linear with Microcell Lens	30D 30° Distribution	DIM10 0-10V Dimming	48 48VDC	425L 425 lumens per foot	27K 2700K	90	BK Black Finish, Black Housing
FRM-606-6 77" Linear with Microcell Lens	55D 55° Distribution	BLE-CASAMBI Bluetooth Low Energy Casambi			30K 3000K		
					35K 3500K		
					40K 4000K		
		TUY TUYA					

DESCRIPTION

The Dual-Hole Linear Module with Microcell Distribution Lens provides versatile and efficient pendant lighting. Available in lengths of 51" and 77", it delivers up to 2730 lumens with a CRI of 90+ and beam angles of 30° and 55°. This fixture offers various color temperatures and advanced dimming options, all in a sleek black finish.

SPECIFICATIONS DATA

Lumens	425 LM/ft
Size(s)	7/8" W x 51"/77" L
Efficacy	70 LM/W
Finish(es)	Black
Driver(s)	0-10V, DALI-2, Tuya, CASAMBI
Input Voltage	48V
Beam Angle	30°, 55°
Mounting Height	Adjustable up to 59"
CRI	>90
CCT	27K, 30K, 35K, 40K
Power (W)	6 W/ft

