

MidiMax

Track Mounted LED Wallwasher

LX2-W



W

Applications

MidiMax has the cleanest profile, designed with the driver concealed within the housing, and is available in RGBW and a range of beam spreads. MAX is a family of gracefully proportioned cylinders designed for low to very high ceilings.

Features

- A concealed swivel provides 385° horizontal rotation and 0-90° tilt. The swivel is permanently tensioned, allowing the luminaire to remain fixed at the desired angle
- A hammertone aluminum reflector and a 40° x 70° spread lens deliver an even floor-to-ceiling, side-to-side wash of light
- The assembly is keyed relative to luminaire housing to retain critical lens orientation

Wallwash (W)

- The internal reflector kicks light vertically up to the ceiling line and down to the floor, while the 40° x 70° spread lens extends the beam in two directions
- A uniquely designed lens and precisely spun reflector enables a 1:1 spacing ratio for unparallelled uniformity

Notable Projects

Kimbell Museum
Baltimore Museum of Art
Duke University West Campus

Complete Family

Standard (LX2), Narrow Spot (LX2-NSP), Wallwash (LX2-W)

Lumens

900, 1200, 1500, 2000, 2500

CCT

27K, 30K, 35K, 40K

CRI

90+ Standard, XIA-95+

SDCM

2-Step MacAdam Ellipse

Finish

White, Black, Silver, RAL

Dimming

DIMTR, BLE, DIMTR-IDM

Voltage

120V, 277V (Non-Dimmable)

Control Capabilities

IDM, Bluetooth

Lifetime

L70 at 50000 Hours

Weight (lbs)

4

Listing

cSAus, c-UL-us



Track Mounted LED Wallwasher

EXAMPLE: **LX2-W-900L-27K-90-DIMTR-120V-WH**

Series	Lumens	CCT	CRI	Driver	Voltage	Finish	Options	Optical Accessories
LX2-W	900L	27K	90+	DIMTR	120V	WH	-	-
	1200L	30K	XIA-95+	NON-DIM	277V	BK	SW	OA-LX2-W-LRS67
	1500L	35K		BLE	(Non-Dim Only)	SI	SB	OA-LX2-W-LRS50
	2000L	40K		DIMTR-IDM		RAL		
	2500L			(Integral Rotary Dimming Module)				

Note: All extra optical accessories, aperture assemblies, and optics can be ordered separately. Check [EPL Website](#) for ordering nomenclature.

Track Adaptor – Fully Concealed, Durable Locking

- Stainless steel clips lock fixture into our specially designed track systems. Two ‘click’ sounds indicate the fixture is secured into the track system
- Clips bite into aluminum, giving extremely durable ground connection
- Edison Price Lighting track systems are designed to completely conceal the adaptor for a clean profile
- Adaptors are shipped standard with all track fixtures. A Eutrac track adaptor can be used for mounting to Eutrac; 0-10V and DALI compatibility available. Contact factory for details

Seamless Installation

Fixtures may be configured to mount to any Edison Price Lighting recessed, suspended, surface-mounted track systems: [Sightline](#), [Highline](#), [Upline](#), [Autobus](#), [Eutrac](#), and [Unicop](#).

Anodized Construction

Heatsink is fabricated from extruded aluminum then undergoes a meticulous anodization process for a permanent and beautiful finish – increasing corrosion and heat resistance for long-lasting durability.

Carefully Applied, Low-VOC Finish

All Edison Price Lighting track fixtures are painted standard with low-VOC water-based paint – diminishing the release of toxic fumes – enhancing air quality and occupant health (unlike solvent-based paint).

Optical Accessories

- OA-LX2-W-LRS67** (67% Light Reduction Screen) - Reduces light by 67%, emitting 33% of total light; alternative to dimming
- OA-LX2-W-LRS50** (50% Light Reduction Screen) - Reduces light by 50%, emitting 50% of total light; alternative to dimming
- OA-LX2-W-DBL** (Daylight Blue) - Simulates daylight; ideal for museums, residential, & commercial
- OA-LX2-W-PK** (Surprise Pink) - Complements skin tones; perfect for hospitality applications
- OA-LX2-W-AMB** - Amber Color Filter
- OA-LX2-W-BL** - Blue Color Filter
- OA-LX2-W-GR** - Green Color Filter
- OA-LX2-W-RD** - Red Color Filter
- OA-LX2-W-RAL** (Rosco Custom Color) - Consult factory for a brilliant Rosco filter in any color. Click [here](#) to see more information on color filters selection

XIA-95+ (Xicato)

- XTM Artist Series, XIM Integral Bluetooth Module (BLE + LED), or XOB (COB array light source in as small as 4.5mm form and up to 8300 lumens)
- Best color-matching: within 1 x 2 MacAdam Ellipse
- Up to 95+ CIE CRI
- Module varies by product family and fixture function.

BLE Xicato Bluetooth Integral Module

Powered by Xicato XIM, the intelligent LED module controllable via a smart device with iOS- or Android-based apps.

- Dimmable down to 0.1%
- Meets IEEE 1789 recommendations for flicker
- Group or individual remote control via a slide switch
- Bluetooth and IDM can be specified in the same fixture, to allow switching between the two options

IDM (Integral Dimming Module) Option

- 120V track only; dim down to 10% using an integral rotary dimmer on the driver case
- Spring-loaded dimmer control shaft can be depressed flush with the driver case to enforce dimmer setting. ‘Clock face’ markings register dimmer setting

Options

- Option for on/off rocker switch on top of fixture, for 120V track only

Driver

120/277V 50/60Hz; Flicker-free 1% dimming standard; THD < 20%; power factor >.09. Thermally protected.

Dimming & Driver Information

DIMTR - Triac, incandescent, and electronic low voltage (ELV) dimming down to 5% in 120V only

NON-DIM - 120 or 277V Non-Dimming Control

BLE - Xicato XIM Bluetooth Integral Module/Xicato XID Intelligent Driver (Consult Factory For Info)

DIMTR-IDM - Integral Rotary Dimming Module

Warranty

Five-year warranty not including providing extraordinary means of access, such as scaffolding or lifts, to service our products.

Listings

- cSAus
- c-UL-us



MidiMax

Track Mounted LED Wallwasher

LX2-W

