

# MiniMax

## Track Mounted MR16 LED Wallwasher

MM-16E-W



w

### Applications

MiniMax 16E W is a wallwasher for use with MR16 retrofit LED lamps. MAX is a family of gracefully proportioned cylinders designed for low to very high ceilings.

### Features

- A hammertone aluminum reflector and a 40° x 70° spread lens deliver an even floor-to-ceiling, side-to-side wash of light
- Assembly is keyed relative to luminaire housing, to retain critical lens orientation
- Full Aiming: A concealed swivel provides 385° horizontal rotation and vertical adjustment from 0° to 90°. The swivel is permanently tensioned, allowing the fixture to remain fixed at the desired angle. Lock fixture into precise angle via a lever lock

**Complete Family** | Standard (MM-16E), Wallwash (MM-16E-W)

**SDCM** | 2-Step MacAdam Ellipse

**Functionality** | Wallwash

**Finish** | White, Black, Silver, RAL

**Voltage** | 120V

**Lifetime** | L70 at 50000 Hours

**Weight (lbs)** | 4

**Listing** | cSAus, c-UL-us



# MiniMax

## Track Mounted MR16 LED Wallwasher

MM-16E-W

EXAMPLE: **MM-16E-W-120V-WH**



<b>MM-16E-W</b>	<b>120V</b>	<b>WH</b>	-
	<b>BK</b>	<b>OA--SL40X70</b>	
	<b>SI</b>	<b>OA--LRS67</b>	
	<b>RAL</b>	<b>OA--LRS50</b>	

**Note:** All extra optical accessories, aperture assemblies, and optics can be ordered separately. Check [EPL Website](#) for ordering nomenclature.

### Interchangeable Optical Accessories

- Combine optical accessories to effortlessly alter visual effects in the field
- The optical assembly accepts up to 2 optical accessories

### Track Adaptor – Fully Concealed, Durable Locking

- Stainless steel clips lock fixture into our specially designed track systems. Two 'click' sounds indicate the fixture is secured into the track system
- Clips bite into aluminum, giving extremely durable ground connection
- Edison Price Lighting track systems are designed to completely conceal the adaptor for a clean profile
- Adaptors are shipped standard with all track fixtures. A Eutrac track adaptor can be used for mounting to Eutrac; 0-10V and DALI compatibility available. Contact factory for details

### Seamless Installation

Fixtures may be configured to mount to any Edison Price Lighting recessed, suspended, surface-mounted track systems: [Sightline](#), [Highline](#), [Upline](#), [Autobus](#), [Eutrac](#), and [Unicep](#).

### Anodized Construction

Heatsink is fabricated from extruded aluminum then undergoes a meticulous anodization process for a permanent and beautiful finish – increasing corrosion and heat resistance for long-lasting durability.

### Carefully Applied, Low-VOC Finish

All Edison Price Lighting track fixtures are painted standard with low-VOC water-based paint – diminishing the release of toxic fumes – enhancing air quality and occupant health (unlike solvent-based paint).

### Optical Accessories

- OA--SL40X70** (40° x 70° Spread Lens) - Delivers a rectangular beam recommended for illuminating wider artwork
- OA--LRS67** (67% Light Reduction Screen) - Reduces light by 67%, emitting 33% of total light; alternative to dimming
- OA--LRS50** (50% Light Reduction Screen) - Reduces light by 50%, emitting 50% of total light; alternative to dimming
- OA-MM-16E-W-DBL** (Daylight Blue) - Simulates daylight; ideal for museums, residential, & commercial
- OA-MM-16E-W-PK** (Surprise Pink) - Complements skin tones; perfect for hospitality applications
- OA-MM-16E-W-AMB** - Amber Color Filter
- OA-MM-16E-W-BL** - Blue Color Filter
- OA-MM-16E-W-GR** - Green Color Filter
- OA-MM-16E-W-RD** - Red Color Filter
- OA-MM-16E-W-RAL** (Rosco Custom Color) - Consult factory for a brilliant Rosco filter in any color. Click [here](#) to see more information on color filters selection

### Driver

Fixture is cULus-listed for mounting on Edison Price Lighting 120V track only.

### Dimming & Driver Information

Consult the lamp manufacturer for dimming compatibility.

### Warranty

Five-year warranty not including providing extraordinary means of access, such as scaffolding or lifts, to service our products.

### Listings

- cSAus
- c-UL-us

