

Project

Date

Product Code

Type

Designer



MADE IN USA


[Click Here](#)

# ARTIMA® 38E O-OBM

surface mounted PAR 38 LED accent light

## FEATURES

- **Artima 38E O-OBM is an accent light** which has been checked for fit and initial operation with the following PAR 38 LED retrofit lamps (supplied by others):
  - KETRA S38
  - Soraa PAR38
  - GE PAR38
  - TCP Allusion PAR38, dim-to-warm
  - Additional lamps may be suitable. Contact factory with inquiries.
- **Fixture is designed for mounting on a 4" octagonal outlet box** (by others).
- **The optical assembly for Artima 38 O-OBM is a matte black cross-baffle** which reduces spill light and controls lamp brightness. This assembly and its setting, are entirely undisturbed by relamping.
- **A flared socket cap and light shield ring prevent any backsplash of light onto the ceiling.**
- **Artima 38E O-OBM fixtures provide 385° horizontal rotation and vertical adjustment from 0° to 90°.** Lamp focus can be locked by tightening two collar clamps using a 3/64" hex key.
- **Artima 38E O-OBM fixtures accept one or two of a number of [Optical Accessories](#)** including spread lenses, a beam smoother, color filters and light reduction screens.
- **Standard finish is matte white with a white socket lead**; also available in black and Industrial Silver matte paint finishes.
- **For more information, [click here](#).**



## APPLICATIONS

Fixture is suitable for 120-volt electrical service and cULus listed for mounting on a standard 4" octagonal outlet box (by others).

### LAMPS BY OTHERS

Edison Price Lighting does not include lamps and does not sell either lamps or their accessories.

### DIMMING

For dimming compatibility consult the lamp manufacturer's website.

### WIRELESS LIMITATIONS

The wireless range of lamped fixtures will vary with lamp and site conditions.

## PRODUCT CODE

Complete Product Code..... ART 38 O-OBM  
standard finish: matte white with white socket lead

## OPTIONS

Specify by adding to the product code.

**matte black** housing finish

black socket lead standard ..... – BLK

**Industrial Silver** housing finish

black socket lead standard ..... – SIL

**custom color** paint housing finish

specify white or black socket lead ..... – WSLV or – BSLV  
and identify color in specification ..... CCH

## OPTICAL ACCESSORIES

Specify as separate line items.

All are 4 3/4" (121mm) dia. Lenses and filters are glass; screens are aluminum.

30° spread lens ..... LENS/4.75-30

30° Daylight Blue spread lens ..... DAY LENS/4.75-30

20° x 55° spread lens ..... LENS/4.75

55° Daylight Blue spread lens ..... DAY LENS/4.75

70° spread lens ..... LENS/4.75-70

prismatic lens (Solite) ..... PLS/4.75

40° x 70° spread lens ..... LENS/4.75-4070

beam smoother ..... CLR/4.75

### color filters

Daylight Blue ..... DAY/4.75

Surprise Pink ..... PNK/4.75

amber ..... AMB/4.75

blue ..... BLU/4.75

green ..... GRN/4.75

red ..... RED/4.75

33% light reduction screen ..... SCR33/4.75

50% light reduction screen ..... SCR50/4.75



41-50 22<sup>ND</sup> STREET, LIC NY 11101 TEL 718.685.0700 FAX 718.786.8530 www.epl.com

©Copyright, Edison Price Lighting 2019

®Artima is a registered trademark of Edison Price Lighting

LED 0-327 10:19

# ARTIMA 38E O-OBM

---



For current lamp performance data, consult lamp manufacturer's website.