


FOUR NSP AA ES recessed LED narrow spot accent light

PRECISE OPTICS - PRECISE OPTICS



- FOUR NSP AA ES is a 4" aperture, enhanced shielding (ES), LED narrow spot accent light. Luminaire is powered by one of a number of Xicato XTM (9mm) LED modules. See tables below for wattages and efficacies. Luminaire may be ordered with one of a number of drivers.
- Luminaire provides 362° horizontal rotation and 0°-35° angular adjustment. Once focused, adjustment is locked by a thumb screw and wing nut.
- Luminaire employs an internal 'twist and lock' reflector to produce an initial beamspread of 14° or 24°. To allow beamspread to be changed in installed luminaires, internal reflectors are available as accessories.
- Luminaire includes a complimentary Beam Smoother which may be replaced by one or two Optical Accessories including lenses and screens.
- External reflectors, cut at 15° with minimal top aperture and deep shielding angle, are available in natural aluminum finishes – semi-specular (C), slightly diffuse (V) or fully diffuse (EC) – as well as black Alzak® and specular white enamel. Other finishes are available on special order. A LightPlate may be used instead of an external reflector.
- LightCharms® or LightPlate™ decorative trims may be ordered instead of standard reflectors, see below.
- Luminaire may be converted to a downlight in the field by re-setting the angular adjustment yoke and replacing the standard external reflector with an optional 0° cut reflector.
- Housing is constructed from 20-gauge electro-zinc, polyester-coated steel in Edison Price Lighting's American factory. Heavy-gauge metals and American manufacturing guarantee long-lasting durability.
- Luminaire includes a pair of mounting bars (3/4" x 27" C channel). Specialty bars for wood and T-bar installations are also available.
- For more information, [click here](#).

APPLICATIONS

Luminaire is listed as an inherently protected luminaire for Damp Location. Luminaire is RoHA compliant, is suitable for use in a fire rated ceiling and is approved for ten #12 wire 90° C branch circuit wiring. Removal of the external reflector allows access to the LED module and junction box.

For a version of this luminaire designed to provide less shielding of the light source and greater efficacy, see [FOUR NSP AA EE](#).
 For higher lumen packages and lower pricing, see [FOUR HI CZS AA](#).
 For narrower beamspreads, see [FIVE HI CLT VNSP](#).
 For shallower depths and lower pricing, see [WAFFER/4AA](#).

SPACING – Three models – L10A, L13S and L13V – must be spaced 30" apart and 15" from walls with 1/2" clearance above housing.

PRODUCT CODE

For complete product code, list basic unit and select one item from each following box.

Basic Unit	FR-XTS-AA
Internal Reflector <i>Choose one.</i>	
14° initial beamspread	14D
24° initial beamspread	24D
Driver	
dimmable to 1% by a 0-10V dimmer on 120 or 277-volt service	DMV
dimmable to 5% or 10% (see Light Output box below) by either an incandescent or ELV dimmer; 120-volt service only	DMP
dimmable to 1% by a 2-wire Lutron compatible dimmer	DMHU
dimmable to 1% SoftOn/FadeToBlack by a Lutron EcoSystem control; <u>not</u> available with L07S, L07V, L10A, L13S or L13V models	ECO-LU
eldoLED 0-10V (Logarithmic) driver dimmable to 0.1% with a 0-10V dimmer on 120 or 277-volt service	DVOELG
eldoLED 0-10V (Linear) driver dimmable to 0.1% with a 0-10V dimmer on 120 or 277-volt service	DVOELN
eldoLED driver dimmable to 0.1%, compatible with DALI control system	DA0-EL
Moons' driver dimmable to 0.1%, compatible with DMX controllers	DX0

Light Source Output (Lumens)	
700L / CRI 98 Artist	DMP (5%) ...- L07A
700L / CRI 80+	DMP (10%) ...- L07S
700L / CRI 80+ Vibrant	3000K only ... DMP (10%) ...- L07V
1000L / CRI 98 Artist	see SPACING
1000L / CRI 80+	DMP (5%) ...- L10A
1000L / CRI 80+	DMP (5%) ...- L10S
1000L / CRI 80+ Vibrant	3000K only ... DMP (5%) ...- L10V
1300L / CRI 80+	see SPACING
1300L / CRI 80+ Vibrant	see SPACING ... 3000K only ... DMP (5%) ...- L13S
1300L / CRI 80+ Vibrant	see SPACING ... 3000K only ... DMP (5%) ...- L13V

Light Color	
2700 K	27K
3000 K	30K
3500 K	35K
4000 K	40K

External Reflector Color and Trim	<i>Overlap</i>	<i>Trim Flush*</i>
Semi-specular Clear	ES-COL	ES-CTF
Slightly diffuse Clear	ES-VOL	ES-VTF
Fully diffuse Clear	ES-ECOL	ES-ECTF
Black	ES-BOL	ES-BTF
White	ES-WOL	ES-WTF

Standard reflector flange continues reflector finish. White painted flanges and custom painted flanges are available on special order. Add WF (white flange) or CCF (custom color flange).

*Trim Flush reflector requires the use of a **plaster ring** Accessory (see below).
 ▶ Reflectors detailed for metal or wood ceilings available on special order.
 A LightPlate may be ordered instead of the standard reflectors above.
 LightPlate **Downlight Spot**, white

OPTIONS *Specify by adding to the basic unit.*

0° cut downlight reflector	0
Millwork trim detail consists of an aperture collar (see below) and a Trim Flush (TF) external reflector (see above). <i>Note: a Plaster Ring is <u>not</u> required.</i>	
milled aluminum aperture collar	M
white aperture collar	MWH
black aperture collar	MBL
custom color aperture collar	MCC
Remote emergency battery pack including two components – battery pack and plate with test switch and light – to be mounted adjacent to luminaire; for use in accessible ceilings	
	RX

EXTRA REFLECTORS *Specify as separate line items.*

14° internal reflector	XTM-REF14-50
24° internal reflector	XTM-REF24-50

ACCESSORIES *Specify as a separate line item.*

Plaster ring allows use of 4 7/8" OD Trim Flush (-TF) reflector in sheetrock ceiling; 5 3/16" dia hole required	TF RING/4
------------------------------------------------------------------------------------------------------------------------------	-----------

OPTICAL ACCESSORIES *Specify as separate line*

All are 2 3/4" (70mm) diameter.

diffuse glass	DGS/2.75
prismatic lens (Solite)	PLS/2.75
55° spread lens	LENS/2.75
40° x 70° spread lens	LENS/2.75-4070
beam smoother	(included with fixture)..... DIF05/2.75
33% light reduction screen	SCR33/2.75
50% light reduction screen	SCR50/2.75

color filters

surprise pink	PNK/2.75
daylight blue.....	DAY/2.75
blue	BLU/2.75
green	GRN/2.75
red	RED/2.75

Downlight Reflectors

Overlap

Trim Flush

Semi-specular Clear	REF-FR-AA-ES-0-COL	REF-FR-AA-ES-0-CTF
Slightly diffuse Clear	REF-FR-AA-ES-0-VOL.....	REF-FR-AA-ES-0-VTF
Fully diffuse Clear	REF-FR-AA-ES-0-ECOL.....	REF-FR-AA-ES-0-ECTF
Black.....	REF-FR-AA-ES-0-BOL.....	REF-FR-AA-ES-0-BTF
White.....	REF-FR-AA-ES-0-WOL.....	REF-FR-AA-ES-0-WTF


Downlight Conversion

Convert to a downlight in the field. Tilt the heatsink assembly to the vertical then shift it to the center of the aperture. Replace angle-cut reflector with 0°-cut **Downlight Reflector** (see OPTIONS).




LIGHTCHARMS & LIGHTPLATES

LightCharms and LightPlates may be used instead of standard reflectors.



EXTERNAL REFLECTOR TRIMS



See below for photometric reports




PHOTOMETRIC REPORT with 14° reflector (tested per IESNA LM-79-2008)

Verification Services Report No. 1177576. Original test report furnished upon request.

Luminaire recessed LED round accent light with semi-specular clear aluminum reflector, LED aimed at 15° above vertical
 Light Source one white Xicato XTM 9mm LES LED with 14° beam spread integral reflector, 3000K CCT, 80 CRI, 1300 lumens

CANDLEPOWER DISTRIBUTION (Candela)

Vertical Angle	Horizontal Angle				
	0	45	90	135	180
0	934	934	934	934	934
5	2242	1544	799	498	387
15	6317	1892	222	18	7
25	1335	357	13	4	2
35	85	16	3	1	1
45	3	2	1	1	1
55	0	1	0	0	0
65	0	0	1	0	0
75	0	0	0	0	0
85	0	0	0	0	0
90	0	0	0	0	0



LUMINAIRE LIGHT OUTPUT AND EFFICACY

LED Light Engine	Luminaire Light Output	Luminaire CBCP	Luminaire Efficacy (lms/watt)	System Wattage	RX Light Output (90 min. run)
700 Lumens Artist	325*	3596*	21*	15	118*
1000 Lumens Artist	424*	4684*	22*	19	118*
700 Lumens standard & Vibrant	338*	3735*	33*	10	178*
1000 Lumens standard & Vibrant	448*	4958*	30*	15	178*
1300 Lumens standard & Vibrant	592	6548	32	19	178*

*estimated values


PHOTOMETRIC REPORT with 24° reflector (tested per IESNA LM-79-2008)

Verification Services Report No. 1177578. Original test report furnished upon request.

Luminaire recessed LED round accent light with semi-specular clear aluminum reflector, LED aimed at 15° above vertical
 Light Source one white Xicato XTM 9mm LES LED with 24° beam spread integral reflector, 3000K CCT, 80 CRI, 1300 lumens

CANDLEPOWER DISTRIBUTION (Candela)

Vertical Angle	Horizontal Angle				
	0	45	90	135	180
0	1067	1067	1067	1067	1067
5	2154	1644	956	613	477
15	3998	1686	299	27	14
25	2038	553	19	4	2
35	295	36	3	1	1
45	14	4	1	0	0
55	0	1	0	0	0
65	0	0	0	0	0
75	0	0	0	0	0
85	0	0	0	0	0
90	0	0	0	0	0



LUMINAIRE LIGHT OUTPUT AND EFFICACY

LED Light Engine	Luminaire Light Output	Luminaire CBCP	Luminaire Efficacy (lms/watt)	System Wattage	RX Light Output (90 min. run)
700 Lumens Artist	325*	2197*	21*	15	118*
1000 Lumens Artist	423*	2862*	22*	19	118*
700 Lumens standard & Vibrant	337*	2282*	33*	10	177*
1000 Lumens standard & Vibrant	447*	3029*	30*	15	177*
1300 Lumens standard & Vibrant	591	4000	31	19	177*

*estimated values

STANDARD DMV DRIVER INFORMATION (UL Class 2, dry and damp location)

Voltage	120	277
Input Watts (L07A/L10A/L07S&V/L10S&V/L13S&V)	15/19/10/15/19	15/19/10/15/19
Input Current (A) (L07A/L10A/L07S&V/L10S&V/L13S&V)	.13/.16/.08/.13/.16	.05/.07/.04/.05/.07
Output Current (mA)	350-700	350-700
Min. Power Factor	.99	.99
Operating Temperature Range (F)	-13 to 122	-13 to 122

LIGHT OUTPUT MULTIPLIER

LED Light Engine	Light Output Multiplier	RX Light Output Multiplier
700 Lumens Artist	.55*	.20*
1000 Lumens Artist	.72*	.20*
700 Lumens standard & Vibrant	.57*	.30*
1000 Lumens standard & Vibrant	.76*	.30*
1300 Lumens standard & Vibrant	1	.30*

*estimated values

REFLECTOR COLOR MULTIPLIERS

Semi-specular clear (C)	1
Slightly diffuse clear (V)	.95
Fully diffuse clear (EC)	.88
Champagne gold clear (G)	.95
Black (B)	.49