

Project

Type



MADE IN USA

[Click Here](#)

Date

Product Code

Designer

# EPIC WAFER/4 AA ES

recessed IC LED accent light

SHALLOW - SHALLOW - SHALLOW - SHALLOW - SHALLOW - SHALLOW - SHALLOW



## FEATURES

- **EPIC WAFER/4 AA ES is a 4" aperture, enhanced shielding, LED accent light (ES)** designed for insulation contact (IC) and certified airtight under ASTM E283. **Recess depth is only 4 5/8"**.
- **Luminaire is powered by one of a number of Cree Chip on board LEDs.** See below for wattages and efficacies.
- **Luminaire provides 365° rotation and 0°-30° angular adjustment.** Once focused, adjustment may be locked by a lever and a thumb nut.
- **Luminaire employs an internal spring-loaded lens** to produce an initial beam-spread of either 12°, 20° or 36°. To allow beam-spread to be changed in installed luminaires, internal lenses are available as accessories.
- **External reflectors, cut at 15°, are available in three clear natural aluminum colors** – semi-specular (C), slightly diffuse (V) or fully diffuse (EC) – as well as champagne gold, black Alzak® and specular white enamel. Other finishes are available on special order.
- **Housing is constructed from 20-gauge electro-zinc, polyester-coated steel** in Edison Price Lighting's American factory. Heavy-gauge metals, an additional protective coating, and American manufacturing guarantees long-lasting durability.
- **EPIC WAFER/4 AA ES includes a pair of residential mounting bars extendable to 20"** and designed for use in wood joists.
- **For more information, [click here](#).**

## APPLICATIONS

Luminaire is listed for direct contact with insulation, certified airtight under ASTM E283, and suitable for damp location. Luminaire is prewired, suitable for use in a fire rated ceiling, and approved for #12 wire 75° C branch circuit wiring. Removal of the external reflector allows access to the LED module and junction box.

For **greater efficacy** and **less shielding** of the light source, see [EPIC WAFER/4 AA EE](#)  
**Standard recessed round aperture**, see [WAFER/4 AA ES](#)  
**Install-from-below**, see [PRESTO WAFER/3 AA ES](#)

## PRODUCT CODE

For complete product code, list basic unit and select one item from each following box.

<b>Basic Unit</b> .....	W4IC-CLT-AA	
<b>Internal Lens</b> <i>Choose one.</i>		
12° initial beamspread .....	-	12D
20° initial beamspread .....	-	20D
36° initial beamspread .....	-	36D
<b>Light Source Output (Lumens)</b>		
800 lumens / CRI 90+ .....	2700K & 3000K only.....	- L08H
1000 lumens .....	2700K & 3000K only.....	- L10H
1200 lumens .....	2700K & 3000K only.....	- L12H
1000 lumens / CRI 80+ .....		- L10S
1200 lumens .....		- L12S
1500 lumens .....		- L15S
<b>Driver</b>		
dimmable to 1% by a 0-10V dimmer on 120 Or 277-volt service.....	-	DMV
dimmable to 5% by either an incandescent or electronic low voltage dimmer only; 120-volt service only.....	-	DMP
dimmable to 1% by a 2-wire Lutron compatible dimmer .....	-	DMI-LU
dimmable to 1% SoftOn/FadeToBlack by a Lutron EcoSystem control.....	-	ECO-LU
eldoLED 0-10V (Logarithmic) driver dimmable to 0.1% with a 0-10V dimmer .....	-	DVOELG
eldoLED 0-10V (Linear) driver dimmable to 0.1% with a 0-10V dimmer .....	-	DVOELN
eldoLED driver dimmable to 0.1% with DALI control system .....	-	DAO-EL
Moons' driver dimmable to 0.1% by DMX controllers .....	-	DX0-MN
<b>Light Color</b>		
2700 K.....	-	27K
3000 K.....	-	30K
3500 K.....	-	35K
4000 K.....	-	40K
<b>External Reflector Color and Trim</b>		
	<i>Overlap</i>	<i>Trim Flush*</i>
Semi-specular Clear .....	ES-COL .....	ES-CTF
Slightly diffuse Clear .....	ES-VOL.....	ES-VTF
Fully diffuse Clear .....	ES-ECOL.....	ES-ECTF
Champagne Gold.....	ES-GOL.....	ES-GTF
Black.....	ES-BOL.....	ES-BTF
White.....	ES-WOL.....	ES-WTF
Standard reflector flange continues reflector finish. White painted flanges and custom painted flanges are available on special order. Add WF (white flange) or CCF (custom color flange).		
*Trim Flush reflector trim requires the use of a <b>plaster ring</b> Accessory (see below).		

## OPTIONS

*Specify by adding to the basic unit.*

0° cut <b>downlight reflector</b> .....	-	0
---	---	---

## EXTRA INTERNAL LENSES

*Specify as separate line items.*



<b>12° internal lens</b> .....	CLT-LENS12-50
<b>20° internal lens</b> .....	CLT-LENS20-50
<b>36° internal lens</b> .....	CLT-LENS36-50

## ACCESSORIES

*Specify as a separate line item.*

<b>Plaster ring</b> allows use of 4 7/8" OD Trim Flush (-TF) reflector in sheetrock ceiling; 5 3/16" dia hole required.....	TF RING/4
---	-----------





**STANDARD DMV DRIVER INFORMATION** (UL Class 2, dry and damp location)

Voltage	120	277
Input Watts (L08H/L10H/L12H/L10S/L12S/L15S)	9/10/13/9/10/13	9/10/13/9/10/13
Input Current (A) (L08H/L10H/L12H/L10S/L12S/L15S)	08/08/11/08/08/11	03/04/05/03/04/05
Output Current (mA)	350-700	350-700
Min. Power Factor	.99	.99
Operating Temperature Range (F)	-13 to 122	-13 to 122

**LIGHT OUTPUT MULTIPLIER**

LED Light Engine	Light Output Multiplier
800 Lumens 90 CRI	0.65*
1000 Lumens 90 CRI	0.78*
1200 Lumens 90 CRI	1
1000 Lumens 80 CRI	0.81*
1200 Lumens 80 CRI	0.96*
1500 Lumens 80 CRI	1.20*

\*estimated values

**REFLECTOR COLOR MULTIPLIERS**

Slightly diffuse clear (V)	1
Fully diffuse clear (EC)	.90
Champagne gold clear (G)	1
Specular white (W)	.70
Black (B)	.40

– photometrics continued below –




## PHOTOMETRIC REPORT with 12° lens (tested per IESNA LM-79-2008)

Verification Services Report No. 11827425.02. Original test report furnished upon request.

Luminaire ..... recessed LED round accent light with semi-specular clear aluminum external reflector, LED aimed at 15° above vertical.  
 Light Source ..... Cree CXB1310 LED with 12° beam spread integral lens, 2700K CCT, 90 CRI, 1200 lumens

### CANDLEPOWER DISTRIBUTION (Candela)



### LUMINAIRE LIGHT OUTPUT AND EFFICACY

LED Light Engine	Luminaire Light Output	Luminaire CBCP	Luminaire Efficacy (lms/watt)	System Wattage	RX Light Output (90 min. run)
800 Lumens 90 CRI	413*	4353*	46*	9	267*
1000 Lumens 90 CRI	496*	5224*	50*	10	267*
1200 Lumens 90 CRI	636	6697	49	13	267*
1000 Lumens 80 CRI	515*	5425*	57*	9	324*
1200 Lumens 80 CRI	611*	6429*	61*	10	324*
1500 Lumens 80 CRI	763*	8036*	59*	13	324*


\*estimated values

## PHOTOMETRIC REPORT with 20° lens (tested per IESNA LM-79-2008)

Verification Services Report No. 11827425.04. Original test report furnished upon request.

Luminaire ..... recessed LED round accent light with semi-specular clear aluminum external reflector, LED aimed at 15° above vertical.  
 Light Source ..... Cree CXB1310 LED with 20° beam spread integral lens, 2700K CCT, 90 CRI, 1200 lumens

### CANDLEPOWER DISTRIBUTION (Candela)



### LUMINAIRE LIGHT OUTPUT AND EFFICACY

LED Light Engine	Luminaire Light Output	Luminaire CBCP	Luminaire Efficacy (lms/watt)	System Wattage	RX Light Output (90 min. run)
800 Lumens 90 CRI	471*	2239*	52*	9	304*
1000 Lumens 90 CRI	565*	2686*	56*	10	304*
1200 Lumens 90 CRI	724	3444	56	13	304*
1000 Lumens 80 CRI	586*	2790*	65*	9	369*
1200 Lumens 80 CRI	695*	3306*	69*	10	369*
1500 Lumens 80 CRI	869*	4133*	67*	13	369*


\*estimated values

## PHOTOMETRIC REPORT with 36° lens (tested per IESNA LM-79-2008)

Verification Services Report No. 11827425.06. Original test report furnished upon request.

Luminaire ..... recessed LED round accent light with semi-specular clear aluminum external reflector, LED aimed at 15° above vertical.  
 Light Source ..... Cree CXB1310 LED with 36° beam spread integral lens, 2700K CCT, 90 CRI, 1200 lumens

### CANDLEPOWER DISTRIBUTION (Candela)



### LUMINAIRE LIGHT OUTPUT AND EFFICACY

LED Light Engine	Luminaire Light Output	Luminaire CBCP	Luminaire Efficacy (lms/watt)	System Wattage	RX Light Output (90 min. run)
800 Lumens 90 CRI	541*	1435*	60*	9	349*
1000 Lumens 90 CRI	649*	1721*	65*	10	349*
1200 Lumens 90 CRI	832	2207	64	13	349*
1000 Lumens 80 CRI	674*	1788*	75*	9	424*
1200 Lumens 80 CRI	798*	2119*	80*	10	424*
1500 Lumens 80 CRI	998*	2648*	77*	13	424*

\*estimated values