





COMPLETE PRODUCT FAMILY

NEW CONSTRUCTION

ADJUSTABLE

RETROFIT

REMODEL

SHALLOW

HIGH LUMEN

CYLINDER

WET LOC/ IP RATED

IC RATEO

EPD SERIES:

A full family of high-performance architectural downlights, combining exceptional illumination and energy efficiency.

APERTURES

1", 2", 3", 4", 5", 6", 8", 10"

SHAPE

ROUND / SQUARE

FINISH COLORS













WH-WHITE

BK-BLACK

BZ-BRONZE

CL-CLEAR

SHZ-SATIN HAZE

WT-WHEAT

LUMENS

Standard: Up to 8000 Lumens High Lumen: Up to 24000 Lumens

CCT & DYNAMIC PLATFORM

22K, 27K, 30K, 35K, 40K, 50K Dims to Warms: 30K-18K, 30K-22K or 27K-18K Tunable White: 50K-27K or 65K-27K RGB+ Tunable White: 65K-18K

CRI

90+ Standard, Optional 98+

COLOR QUALITY

2 Step MacAdam Ellipse

DISTRIBUTION

NSPO (15"), SPO (24"), NO 30"), MO (36"), MWO (52"), WO (60"), VWO (70")

TRIM OPTIONS

Downlight, Trim-less, Wall Wash,
Double Wall Wash, Corner Wall Wash,
Wet Location

REFLECTOR COLOR

CL (Semi-Specular Chrome), SHZ (Low Indescent Satin Haze), WT (Wheat), W (White), BK (Black), BZ (Bronze)

FLANGE COLOR

WH (Self-Flanged White), SCH (Self-Flanged Semi-Specular Chrome), SHZ (Self-Flanged Low Iride<u>sc</u>ent Satin Haze), BK (Self-Flanged Black), BZ (Self-Flanged Bronze)

EMERGENCY

EMG-LED-10W
EMG-LED-20W
INTG-EMG-LED-10W
INTG-EMG-LED-20W
EMG-LED-G2-10W-SOT

LIFETIME

L70 at 102,000 Hours

PHOTOMETRIC TEST

In accordance with IES LM79-08, LM80 and TM-30, TM-21



