

This information is subject to change without notice.

233 Ceiling Mounted Track Series

2~, 120V track w/ Data

Eutrac track may be surface mounted on the ceiling or suspended-mounted by aircraft cable or pendant. Eutrac track may not be mounted on the wall, either vertically or horizontally.

Material: Extruded aluminum profile with two bus bars (crimped PVC-supported profiles).

Contacts: Four rectangular 12-gauge copper conductors for two independent switchable circuits embedded in PVC profiles; rectangular shape provides fuller contact than the standard round contacts.

Data Bus: PVC-supported profile with two embedded 22-gauge cross section nickel-plated conductors. Data information can be picked up anywhere along the track via data bus equipped adapters. The data bus can be used for DALI or 0-10V dimming.

Ground: Through aluminum profile.

7 Point Conductor Track:

L1: Circuit 1

N1: Neutral for circuit 1

L2: Circuit 2

N2: Neutral for circuit 2

G: Ground

PVC Support Profiles: 2 data contacts

AMPs: 20 amps per circuit

Track Features:

Mounting: Pre-punched $\frac{1}{4}$ " x 1" slotted holes, 8" on center. Field drilling can be accomplished to accommodate fixtures or secure points in the ceiling.

Cutting Profile / Track: Using a dry chop saw or hacksaw with miter box, cut all sides perpendicular to insure a flush fit with all accessories and spliced track sections. Do not cut track without these tools. **Bending of contact points not required after field cutting.** Deburr all cut track sections before assembling.


Colors: White, Black, Silver Anodized **Lengths:** 4', 8', 12' (1219mm, 2438mm, 3658)

Track Accessories: All accessories must be ordered as separate items based on the quantity required per configuration.

Ordering:

| Length | Model | White | Black | Silver |
|--------|--------|-------|-------|--------|
| 4' | 233-10 | 1 | 2 | 3 |
| 8' | 233-20 | 1 | 2 | 3 |
| 12' | 233-30 | 1 | 2 | 3 |

Example: 233-201: 8' length, white, w/data



Mounting Profiles:

Standard ceiling mounted track can be used in the following profiles.


Suspended Profile:

459-403: Pendant H Profile

Recessed Profile:

198-50-0012-01: T Bar Profile: ACT (Tile)

198-50-0010-00: Spackle Flange Profile, drywall application.



Option:

88-888-: Track cover (-6 white, -2: black)

