

## SPOT-LIGHT



### FREE SERIES MODULE FEATURES

**Compact Dimensions:**

Diameter 1 5/8" x Height 2 11/16", ideal for discreet installation

**High Efficiency:**

Consumes only 6W of power while providing 375LM / 470LM of light output

**Adjustable Beam Angles:**

Available in 24° and 36° options to provide targeted or broader illumination

**Advanced Dimming and Controls:**

Compatible with Non-dimming, DALI, CASAMBI, and 0-10V systems for versatile control

**Durable Finish:**

Black coating with an IP20 rating, suitable for indoor environments

**Easy Installation:**

Designed for track mounting, ensuring a hassle-free setup

### TRACK MODULE ORDERING GUIDE

Basic Unit	Beam Angle	Driver	Voltage	Lumens	CCT	CRI	Finish
FR-201 1-5/8" Spotlight	<b>24D</b> 24° Distribution	<b>DIM10</b> 0-10V Dimming	<b>48</b> 48VDC	<b>470L</b> 470 lumens	<b>27K</b> 2700K	<b>90</b>	<b>BK</b> Black Finish, Black Housing
	<b>36D</b> 36° Distribution	<b>BLE-CASAMBI</b> Bluetooth Low Energy Casambi		<b>375L</b> 375 lumens	<b>30K</b> 3000K		
		<b>DALI-2</b>			<b>35K</b> 3500K		
		<b>TUY</b> TUYA			<b>40K</b> 4000K		

### DESCRIPTION

The Free Series Track-Mounted LED Spotlight Luminaire offers sleek design and high performance, perfect for versatile indoor lighting applications. With high CRI and multiple CCT options, it ensures vibrant and accurate color rendering with adjustable beam angles.

### SPECIFICATIONS DATA

Lumens	470 / 375
Size(s)	Ø 1-5/8" x 2-11/16" L
Finish(es)	Black
Driver(s)	0-10V, DALI-2, Tuya, CASAMBI
Input Voltage	48V
Beam Angle	24°, 36°
CRI	>90
CCT	27K, 30K, 35K, 40K
Power (W)	6

PIVOT



TILT



