



FREE SERIES MODULE FEATURES

Compact Dimensions:

Diameter 1 3/16" x Length 23 5/8" / 35 7/16" / 47 1/4", ideal for versatile installation

High Efficiency:

Consumes 12W / 18W / 24W of power while providing 1200LM / 1800LM / 2400LM of light output

PC Diffuser:

Provides even and soft light distribution with a 100° beam angle

Advanced Dimming and Controls:

Compatible with Non-dimming, DALI, CASAMBI, and 0-10V systems for versatile control

Durable Finish:

Black coating with an IP20 rating, suitable for indoor environments

Easy Installation

TRACK MODULE ORDERING GUIDE

DESCRIPTION

The Free Series Track-Mounted LED Linear Module combines sleek design with high performance, perfect for versatile indoor lighting applications. With high CRI and multiple CCT options, it ensures vibrant and accurate color rendering with a wide beam angle for even illumination.

SPECIFICATIONS DATA

Lumens	2400 / 1800 / 1200
Size(s)	Ø 1-3/16" x 24, 36, 48"
Finish(es)	Black
Driver(s)	0-10V, DALI-2, Tuya, CASAMBI
Input Voltage	48V
Beam Angle	100°
CRI	>90
ССТ	27K, 30K, 35K, 40K
Power (W)	24 / 18 / 12

PIVOT



Basic Unit	Beam Angle	Driver	Voltage	Lumens	ССТ	CRI	Finish
FR-204-2 24" Adjustable Neon Linear	100D 100° Distribution	DIM10 0-10V Dimming	48 48VDC	2400L 2400 lumens	27K 2700K	90	BK Black Finish, Black Housing
FR-204-3 36" Adjustable Neon Linear		BLE-CASAMBI Bluetooth Low Energy Casambi		1800L 1800 lumens	30K 3000K		
FR-204-4 48" Adjustable Neon Linear		DALI-2		1200L 1200 lumens	35K 3500K		
		TUY TUYA			40K 4000K		



Free Series

FR-204-2/3/4



